

High Wall Heat Pump Ductless System

Indoor Model: D5FSHAH30XAK

Job Data:

Tag #:

Date:

Location:


Carrier#:



- INDOOR STANDARD FEATURES**
- Modes: Cool, Heat, Dry, Fan, Auto
 - Four fan speeds
 - Sleep Mode
 - Turbo Mode
 - Follow Me (senses temperature at handheld remote)
 - Auto-Restart function
 - Quiet indoor operation
 - Anti-corrosive fin coating
 - Factory Pre-Installed Leak Detection System
 - Pipe Connection Size - Liquid : **3/8in(9.52mm)**
 - Pipe Connection Size - Suction : **5/8in(15.9mm)**

- LIMITED WARRANTY***
- Seven (7) years compressor and five (5) years parts warranty.

NOTE: Images for illustration purposes only. Actual models may be slightly different.



INDOOR UNIT DIMENSIONS				
Capacity	Unit	W	D	H
6K/9K/12K	mm	795	225	295
	inch	31.3	8.86	11.61
18K	mm	965	239	319
	inch	37.99	9.41	12.56
24K ~ 36K	mm	1140	275	370
	inch	44.88	10.83	14.57



D5FSHAH30XAK			
System	Indoor Model #		D5FSHAH30XAK
	Indoor Size		30000
Electrical	Voltage, Phase, Cycle		208/230-1-60
	Power Supply		Indoor unit powered by outdoor unit
	MCA	A.	3
Operating Range	Cooling Indoor DB Min - Max		60~90(16~32)
	Heating Indoor DB Min - Max		32~86(0~30)
Indoor Coil	Face Area	Sq. Ft.	3.6
	No. Rows		3
	Fins per inch		20
	Circuits		7
Indoor Unit	Number of Fan Speeds		1050/880/630
	Airflow (highest to lowest)	CFM	882.9 / 635.7 / 506.2 / 382.6 / /
	Sound Pressure (highest to lowest)	dB(A)	53.0/45.5/40/30.5/19.5
	Moisture Removal	L/h	4
	Air Throw Data	ft(m)	30.1(9.18)
Dimensions	Height	in (mm)	14.57(370)
	Width	in (mm)	44.88(1140)
	Depth	in (mm)	10.83(275)
	Net Weight	lbs (kg)	43.21(19.6)
	Shipping Height	in (mm)	13.98(355)
	Shipping Width	in (mm)	48.43(1230)
	Shipping Depth	in (mm)	17.91(455)
	Shipping Net Weight	lbs (kg)	54.67(24.8)
CONTROLS			
Standard	Wireless Remote Controller (*F/°C Convertible)		
Optional	Wired Remote Control 7 Day Programmable		KSACN1401AAA
	Wired Remote Control with Timer Function		KSACN1201AAA
	Wi-Fi™ Kit High Wall		KSAIF0701AAA
	24V Mini Interface		KSAIC0601230



R-454B