

1-Way Cassette Heat Pump Ductless System

Indoor Model: D5FSOAH12XAK

Job Data:

Tag #:

Date:

Location:

Carrier#:




INDOOR STANDARD FEATURES

- Modes: Cool, Heat, Dry, Fan, Auto
- Designed to be mounted between 16" joists
- Four fan speeds
- Sleep Mode
- Follow Me (senses temperature at handheld remote)
- Auto-Restart function
- Quiet indoor operation
- Anti-corrosive fin coating


RESIDENTIAL APPLICATION LIMITED WARRANTY*

- Ten (10) years if properly registered within ninety (90) days after original installation, parts are warranted to the original purchaser for a period of ten (10) years. Otherwise, parts warranty is five (5) years.

NOTE: Images for illustration purposes only. Actual models may be slightly different.



INDOOR UNIT DIMENSIONS				
Capacity	Unit	W	D	H
6K ~ 18K	mm	1278	335	228
	inch	50.31	13.19	8.98



D5FSOAH12XAK			
System	Indoor Model #		D5FSOAH12XAK
	Indoor Size		12000
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208-230/1/60
	Power Supply	Indoor unit powered by outdoor unit	
	MCA	A.	3
Operating Range	Cooling Indoor DB Min - Max	°F(°C)	60~90(16~32)
	Heating Indoor DB Min - Max	°F(°C)	32~86(0~30)
Indoor Coil	Face Area	Sq. Ft.	2.81
	No. Rows		2
	Fins per inch		20
	Circuits		3
Indoor Unit	Number of Fan Speeds		1075/982/797
	Airflow (highest to lowest)	CFM	311.76/282.35/247.06
	Sound Pressure (highest to lowest)	dB(A)	41/37/33/24
	Moisture Removal	L/h	1.69
	Air Throw Data	ft(m)	22.97(7)
Dimensions	Height	in (mm)	8.98(228)
	Width	in (mm)	50.31(1278)
	Depth	in (mm)	13.19(335)
	Net Weight	lbs (kg)	45.19(20.5)
	Shipping Height	in (mm)	22.64(575)
	Shipping Width	in (mm)	57.60(1463)
	Shipping Depth	in (mm)	22.48(571)
	Shipping Net Weight	lbs (kg)	45.19(20.5)
CONTROLS			
Standard	Wireless Remote Controller (°F/°C Convertible)		
Optional	Wired Remote Control 7 Day Programmable		KSACN1401AAA
	Wired Remote Control with Timer Function		KSACN1201AAA
	Wi-Fi™ Kit High Wall		KSAlF0701AAA
	24V Mini Interface		KSAlC0601230



R-454B