

Daikin *OTERRA* (R-32)

Wall-Mounted Heating & Cooling

21 SEER2 | Up to 10.2 HSPF2 | Up to 12.5 EER2



Daikin *OTERRA* Wall Mount Systems provide energy efficiency and comfort control with an affordable, cost-saving solution. Available in both heat pump and cooling only models, these systems feature streamlined, wall-mounted indoor units paired with quiet and compact outdoor units.

Standard Features

- » Energy Efficient – 21 SEER2, 10.2 HSPF2, 12.5 EER2 for ultra-efficient cooling and heating operation and reduced operating costs compared to conventional lower-efficiency systems.
- » Cooling Range: 50°F DB to 118°F DB (10° C DB to 48°C DB); for 9 and 12K, 50°F DB to 122°F DB (10°C DB to 50° C DB); for 18 and 24K. Extended operation to -4°F DB (-20°C DB) with facility setting and wind baffle.
- » Heating Range: 5°F WB - 65°F WB (-15°C WB - 18°C WB)

Optional Features

- » Wired controller
- » Compatible with DKN Residential Cloud Wi-Fi Adaptor or DKN Plus Interface



ECO+ – An intelligent feature that ensures optimum energy consumption while fulfilling basic human comfort needs. Once activated, set temperature will be adjusted automatically to an optimum energy consumption level



Blue Fin Protection – The hydrophilic coated fin ensures the condensate water moves easily to the drain pan — thus enhancing the cleanliness and lifespan of the cooling coil.



Simplified Maintenance – The indoor unit has been re-designed for easier removal of the drain pan, blower wheel, and indoor fan motor (compared to other wall-mounted units).

IDEAL SOLUTIONS FOR:

- » Renovations, remodeling and new construction
- » Sun rooms, basements, attics, garages, hot or cold rooms, and more
- » Rooms where floor space comes at a premium or is not available for other application
- » Ceiling void or attic does not allow for a viable duct run option
- » Cooling Only models are an excellent value for space not requiring heating



Our outdoor unit drain pans have up to 16 holes which allows for effective drainage of condensation. In some case, this improved drain pan design eliminates the need for drain pan heaters, resulting in higher efficiencies in low ambient temperatures.



Daikin **OTERRA (R-32)** With built in Wi-Fi

Wall-Mounted Heating & Cooling

21 SEER2 | Up to 10.2 HSPF2 | Up to 12.5 EER2

Model	Indoor Unit		FTXF09BVJU9		FTXF12BVJU9		FTXF18BVJU9		FTXF24BVJU9	
	Outdoor Unit		RXF09BVJU9		RXF12BVJU9		RXF18BVJU9		RXF24BVJU9	
			Cooling	Heating	Cooling	Heating	Cooling	Heating	Cooling	Heating
Capacity Rated (Min. ~ Max.)	Btu/h		9,000 (4,400 ~ 11,200)	10,000 (4,400 ~ 14,300)	12,000 (4,400 ~ 14,600)	13,500 (4,400 ~ 18,000)	18,000 (6,900 ~ 22,000)	21,600 (5,800 ~ 28,000)	22,400 (7,000 ~ 26,400)	24,000 (6,200 ~ 32,000)
Moisture Removal		gal/h		—		—		—		—
COP Rated			2		2		2		1.9	
EER2 Rated			12.5				12			
SEER2			21							
HSPF2			10.2				9.6		9.5	
Piping	Liquid	in. (mm)	Ø 1/4 (Ø 6.4)							
Connections	Gas		Ø 3/8 (Ø 9.5)				Ø 1/2 (Ø 12.7)		Ø 5/8 (Ø 15.9)	
	Drain		Ø 5/8 (Ø 16.0)							
Max. Interunit Piping Length		ft (m)	65-5/8 (20)				98-1/2 (30)			
Max. Interunit Height Difference			49-1/4 (15)				65-5/8 (20)			
Chargeless			49-1/4 (15)							
Amount of Additional Charge of Refrigerant		oz/ft (g/m)	0.22(20)							
Operating Range - Cooling		°F DB	50 ° - 118 °F				50 ° - 122 °F			
Operating Range - Low-Ambient Cooling*			5 ° - 118 °F				5 ° - 122 °F			
Operating Range - Cooling with Optional Air direction adjustment grille *			-4 ° - 118°F				-4 ° - 122°F			
Operating Range - Heating*			°F WB	5 ° - 65 °F						
Indoor Unit			FTXF09BVJU9		FTXF12BVJU9		FTXF18BVJU9		FTXF24BVJU9	
Airflow Rate	H	cfm (m³/min)	381 (10.8)	385 (10.9)	399 (11.3)	438 (12.4)	565 (16)	717 (20.3)	629 (17.8)	717 (20.3)
	M		272 (7.7)	304 (8.6)	282 (8.0)	319 (9)	463 (13.1)	572 (16.2)	501 (14.2)	572 (16.2)
	L		230 (6.5)	230 (6.5)	219 (6.2)	240 (6.8)	378 (10.7)	452 (12.8)	378 (10.7)	466 (13.2)
	SL		124(3.5)	194 (5.5)	117(3.3)	205 (5.8)	335 (9.5)	388 (11)	335 (9.5)	413 (11.7)
Fan	Speed	Steps	3 Steps, Auto, Quiet, Turbo							
Air Direction Control			Right, Left, Horizontal, Downward							
Air Filter			Removable, Washable							
Dimensions		in.	11-1/4 × 30-5/8 × 8-3/4				11-5/8 X 39-3/8 X 10-3/4			
(H × W × D)		(mm)	(286 X 778 X 223)				(295 X 1000 X 263)			
Weight		Lbs (kg)	19 (9.0)		19 (9.0)		28 (13)			
Sound Pressure Level (H / M / L / SL)		dB(A)	44 / 35 / 30 / 19	41 / 35 / 28 / 25	46 / 37 / 31 / 19	45 / 37 / 30 / 25	48 / 43 / 37 / 33	49 / 42 / 37 / 33	52 / 45 / 38 / 34	49 / 43 / 38 / 34
Outdoor Unit			RXF09BVJU9		RXF12BVJU9		RXF18BVJU9		RXF24BVJU9	
Compressor	Motor	W								
	Output									
Refrigerant	Type		R-32							
	Charge	Lbs (kg)	1.65 (0.75)				2.45 (1.11)			
Airflow Rate	H	cfm (m³/min)	1051 (29.8)	966 (27.4)	1051 (29.8)	966 (27.4)	2327 (65.9)	2327 (65.9)	2327 (65.9)	2327 (65.9)
Dimensions		in.	21-11/16 X 26-1/2 X 11-3/16				29-1/2 X 34-1/4 X 12-5/8			
(H × W × D)		(mm)	(550 × 675 × 284)				(750 X 870 X 320)		(750 X 870 X 320)	
Weight		Lbs (kg)	60 (27)				113 (51)			
Sound Pressure Level	H	dB(A)	46	48	48		54	57	54	57
ENERGY STAR® CERTIFIED			Yes		Yes		Yes		Yes	

*Applicable to heat pump models only, refer to installation manual for more details.

**Cutting a jumper or a dipswitch setting is required. Refer to installation manual.

Unit Combination		Power Supply				Fan/Compressor	Indoor Fan
INDOOR UNIT	OUTDOOR UNIT	Hz - Volts	Voltage Range	MCA	MOCP	Inverter Drive Input	Inverter Drive Input
FTXF09BVJU9	RXF09BVJU9	60 - 208	Min. 60 Hz 187 V	11.6	15	9	0.2
		60 - 230	Max. 60 Hz 253 V				
FTXF12BVJU9	RXF12BVJU9	60 - 208	Min. 60 Hz 187 V	14.6	15	11.4	0.23
		60 - 230	Max. 60 Hz 253 V				
FTXF18BVJU9	RXF18BVJU9	60 - 208	Min. 60 Hz 187 V	21.4	25	17.4	0.4
		60 - 230	Max. 60 Hz 253 V				
FTXF24BVJU9	RXF24BVJU9	60 - 208	Min. 60 Hz 187 V	21.6	25	17.6	0.45
		60 - 230	Max. 60 Hz 253 V				

