

Model	Indoor Unit		FVXV09AVJUW9		FVXV09AVJUT9	
	Outdoor Unit		RXP09AVJU9		RXP09AVJU9	
			Cooling	Heating	Cooling	Heating
Power Supply			1 ϕ, 208 - 230 V, 60 Hz		1 ϕ, 208 - 230 V, 60 Hz	
Capacity Rated (Min. - Max.)	Btu/h		9,000 (3,700 ~ 10,900)	12,000 (4,600 ~ 17,100)	9,000 (3,700 ~ 10,900)	12,000 (4,600 ~ 17,100)
Running Current (Rated)	A		3.70 - 3.35	4.50 - 4.07	3.70 - 3.35	4.50 - 4.07
Power Consumption (Rated)	W		750 - 750	921 - 921	750 - 750	921 - 921
Power Factor (Rated)	%		97.5 - 97.4	98.4 - 98.5	97.5 - 97.4	98.4 - 98.5
SEER2			19.5	—	19.5	—
HSPF2 (Region IV)			—	9.7	—	9.7
HSPF2 (Region V)			—	8.5	—	8.5
EER2 (Rated)	Btu/W-h		12.0	—	12.0	—
COP2 (°F (-15°C))	W/W		—	1.8	—	1.8
Piping Connections	Liquid	in. (mm)	ϕ1/4 (6.4)		ϕ1/4 (6.4)	
	Gas	in. (mm)	ϕ3/8 (9.5)		ϕ3/8 (9.5)	
	Drain	in. (mm)	ϕ13/16 (20)		ϕ13/16 (20)	
Heat Insulation			Both Liquid and Gas Pipes		Both Liquid and Gas Pipes	
Max. Interunit Piping Length	ft (m)		65-5/8 (20)		65-5/8 (20)	
Max. Interunit Height Difference	ft (m)		49-1/4 (15)		49-1/4 (15)	
Chargeless	ft (m)		49-1/4 (15)		49-1/4 (15)	
Amount of Additional Charge of Refrigerant	oz/ft (g/m)		0.22 (20)		0.22 (20)	
Indoor Unit		FVXV09AVJUW9		FVXV09AVJUT9		
Front Panel Color (Mancel No.)			White (N9.5)		Espresso (B-690)	
Heat Exchanger	Rows × Stages, Fin per Inch		2 × 22, 21		2 × 22, 21	
	Fin Spec / Tube		Multi Slit Fin / ϕ5 Hi-XB Tube		Multi Slit Fin / ϕ5 Hi-XB Tube	
Airflow Rate	H / M / L / SL	cfm	297 / 265 / 201 / 173	321 / 261 / 219 / 191	297 / 265 / 201 / 173	321 / 261 / 219 / 191
		m³/min	8.4 / 7.5 / 5.7 / 4.9	9.1 / 7.4 / 6.2 / 5.4	8.4 / 7.5 / 5.7 / 4.9	9.1 / 7.4 / 6.2 / 5.4
Air Direction Control			Right, Left, Upward, Downward		Right, Left, Upward, Downward	
Air Filter			Removable, Washable, Mildew Proof		Removable, Washable, Mildew Proof	
Fan Motor	H / M / L / SL	rpm	650 / 590 / 460 / 410	700 / 580 / 500 / 440	650 / 590 / 460 / 410	700 / 580 / 500 / 440
	Motor output	Hp	0.05		0.05	
Fan	Type		Turbo Fan		Turbo Fan	
Running Current (Rated)	A		0.08 - 0.07	0.10 - 0.09	0.08 - 0.07	0.10 - 0.09
Power Consumption (Rated)	W		9 - 9	11 - 11	9 - 9	11 - 11
Power Factor (Rated)	%		48.0 - 56.3	48.0 - 54.2	48.0 - 56.3	48.0 - 54.2
Temperature Control			Microcomputer Control		Microcomputer Control	
Dimensions (H × W × D)	in. (mm)		23-5/8 × 29-1/2 × 9-3/8 (600 × 750 × 238)		23-5/8 × 29-1/2 × 9-3/8 (600 × 750 × 238)	
Packaged Dimensions (H × W × D)	in. (mm)		29-5/16 × 34-7/16 × 133-5/8 (757 × 874 × 346)		29-5/16 × 34-7/16 × 133-5/8 (757 × 874 × 346)	
Weight (Mass)	lbs (kg)		40 (18)		40 (18)	
Gross Weight (Gross Mass)	lbs (kg)		50 (23)		50 (23)	
Sound Pressure Level (H / M / L / SL)	dB(A)		39 / 36 / 30 / 26	40 / 35 / 31 / 26	39 / 36 / 30 / 26	40 / 35 / 31 / 26
Remote Controller			ARC466A89		ARC466A89	
Outdoor Unit		RXP09AVJU9		RXP09AVJU9		
Casing Color			Ivory White		Ivory White	
Heat Exchanger	Fin Spec / Tube		Waffle Fin (PE) / ϕ7 Hi-XSL Tube		Waffle Fin (PE) / ϕ7 Hi-XSL Tube	
Fan Motor	Motor output	Hp	0.04		0.04	
Compressor	Type		Hermetically Sealed Swing Type		Hermetically Sealed Swing Type	
	Model		2Y147BKBX1A		2Y147BKBX1A	
Refrigerant Oil	Type		FW68DA		FW68DA	
	Charge	oz (L)	21.98 (0.65)		21.98 (0.65)	
Refrigerant	Type		R-32		R-32	
	Charge	lbs (kg)	1.74 (0.79)		1.74 (0.79)	
Airflow Rate	cfm (m³/min)		1,088 (30.8)	1,126 (31.9)	1,088 (30.8)	1,126 (31.9)
Fan	Type		Propeller		Propeller	
Running Current (Rated)	A		3.62 - 3.28	4.40 - 3.98	3.62 - 3.28	4.40 - 3.98
Power Consumption (Rated)	W		741 - 741	910 - 910	741 - 741	910 - 910
Power Factor (Rated)	%		98.4 - 98.3	99.4 - 99.5	98.4 - 98.3	99.4 - 99.5
Dimensions (H × W × D)	in. (mm)		21-15/16 × 26-9/16 × 11-3/16 (557 × 675 × 284)		21-15/16 × 26-9/16 × 11-3/16 (557 × 675 × 284)	
Packaged Dimensions (H × W × D)	in. (mm)		24-7/16 × 31-1/4 × 14-1/8 (620 × 794 × 359)		24-7/16 × 31-1/4 × 14-1/8 (620 × 794 × 359)	
Weight (Mass)	lbs (kg)		72 (33)		72 (33)	
Gross Weight (Gross Mass)	lbs (kg)		77 (35)		77 (35)	
Sound Pressure Level	dB(A)		50	52	50	52
Conditions Based on	Indoor		80.0°FDB (26.7°CDB) / 67.0°FWB (19.4°CWB)	70.0°FDB (21.1°CDB) / 60.0°FWB (15.6°CWB)	80.0°FDB (26.7°CDB) / 67.0°FWB (19.4°CWB)	70.0°FDB (21.1°CDB) / 60.0°FWB (15.6°CWB)
	Outdoor		95.0°FDB (35.0°CDB) / 75.0°FWB (24.0°CWB)	47.0°FDB (8.3°CDB) / 43.0°FWB (6.1°CWB)	95.0°FDB (35.0°CDB) / 75.0°FWB (24.0°CWB)	47.0°FDB (8.3°CDB) / 43.0°FWB (6.1°CWB)
	Piping Length		25 ft		25 ft	
Drawing No.			3D159397A			
Note(s)			SL: The quiet fan level of the airflow rate setting. When indoor unit is connected with multi-system outdoor unit. Please refer to the specifications of the multi-system outdoor unit to be connected.			

Conversion Formulae
kcal/h = kW × 860
Btu/h = kW × 3412
cfm = m³/min × 35.3

Model	Indoor Unit		FVXV12AVJUW9		FVXV12AVJUT9	
	Outdoor Unit		RXP12AVJU9		RXP12AVJU9	
			Cooling	Heating	Cooling	Heating
Power Supply	1 ϕ, 208 - 230 V, 60 Hz				1 ϕ, 208 - 230 V, 60 Hz	
Capacity Rated (Min. - Max.)	Btu/h	12,000 (3,700 ~ 12,600)		14,000 (4,600 ~ 19,900)		
Running Current (Rated)	A	5.58 - 5.05		5.17 - 4.67		
Power Consumption (Rated)	W	1,143 - 1,143		1,060 - 1,060		
Power Factor (Rated)	%	98.5 - 98.4		98.6 - 98.6		
SEER2		19.5		—		
HSPF2 (Region IV)		—		9.5		
HSPF2 (Region V)		—		8.1		
EER2 (Rated)	Btu/W-h	10.5		—		
COP2 (°F (-15°C))	W/W	—		1.8		
Piping Connections	Liquid	in. (mm)	ϕ1/4 (6.4)		ϕ1/4 (6.4)	
	Gas	in. (mm)	ϕ3/8 (9.5)		ϕ3/8 (9.5)	
	Drain	in. (mm)	ϕ13/16 (20)		ϕ13/16 (20)	
Heat Insulation	Both Liquid and Gas Pipes				Both Liquid and Gas Pipes	
Max. Interunit Piping Length	ft (m)	65-5/8 (20)		65-5/8 (20)		
Max. Interunit Height Difference	ft (m)	49-1/4 (15)		49-1/4 (15)		
Chargeless	ft (m)	49-1/4 (15)		49-1/4 (15)		
Amount of Additional Charge of Refrigerant	oz/ft (g/m)	0.22 (20)		0.22 (20)		
Indoor Unit		FVXV12AVJUW9		FVXV12AVJUT9		
Front Panel Color (Mancel No.)	White (N9.5)				Espresso (B-690)	
Heat Exchanger	Rows × Stages, Fin per Inch	2 × 22, 21				
	Fin Spec / Tube	Multi Slit Fin / ϕ5 Hi-XB Tube				
Airflow Rate	H / M / L / SL	cfm	321 / 265 / 201 / 173		321 / 300 / 219 / 191	
		m³/min	9.1 / 7.5 / 5.7 / 4.9		10.5 / 8.5 / 6.2 / 5.4	
Air Direction Control	Right, Left, Upward, Downward				Right, Left, Upward, Downward	
Air Filter	Removable, Washable, Mildew Proof				Removable, Washable, Mildew Proof	
Fan Motor	H / M / L / SL	rpm	700 / 590 / 460 / 410		800 / 660 / 500 / 440	
	Motor output	Hp	0.05			
Fan	Type	Sirocco Fan				
Running Current (Rated)	A	0.10 - 0.09		0.15 - 0.14		
Power Consumption (Rated)	W	11 - 11		16 - 16		
Power Factor (Rated)	%	48.0 - 54.2		48.0 - 50.7		
Temperature Control	Microcomputer Control				Microcomputer Control	
Dimensions (H × W × D)	in. (mm)	23-5/8 × 29-1/2 × 9-3/8 (600 × 750 × 238)				
Packaged Dimensions (H × W × D)	in. (mm)	29-13/16 × 34-7/16 × 13-5/8 (757 × 874 × 346)				
Weight (Mass)	lbs (kg)	40 (18)				
Gross Weight (Gross Mass)	lbs (kg)	50 (23)				
Sound Pressure Level (H / M / L / SL)	dB(A)	41 / 36 / 30 / 26		43 / 38 / 31 / 26		
Remote Controller	ARC466A89				ARC466A89	
Outdoor Unit		RXP12AVJU9		RXP12AVJU9		
Casing Color	Ivory White				Ivory White	
Heat Exchanger	Fin Spec / Tube	Waffle Fin (PE) / ϕ7 Hi-XSL Tube				
Fan Motor	Motor output	Hp	0.04			
Compressor	Type	Hermetically Sealed Swing Type				
	Model	2Y147BKBX1A				
Refrigerant Oil	Type	FW68DA				
	Charge	oz (L)	21.98 (0.65)		21.98 (0.65)	
Refrigerant	Type	R-32				
	Charge	lbs (kg)	1.74 (0.79)		1.74 (0.79)	
Airflow Rate	cfm (m³/min)	1,126 (31.9)		1,126 (31.9)		
Fan	Type	Propeller				
Running Current (Rated)	A	5.48 - 4.96		5.02 - 4.53		
Power Consumption (Rated)	W	1,132 - 1,132		1,044 - 1,044		
Power Factor (Rated)	%	99.3 - 99.2		99.9 - 99.9		
Dimensions (H × W × D)	in. (mm)	21-15/16 × 26-9/16 × 11-3/16 (557 × 675 × 284)				
Packaged Dimensions (H × W × D)	in. (mm)	24-7/16 × 31-1/4 × 14-1/8 (620 × 794 × 359)				
Weight (Mass)	lbs (kg)	72 (33)				
Gross Weight (Gross Mass)	lbs (kg)	77 (35)				
Sound Pressure Level	dB(A)	50		52		
Conditions Based on	Indoor	80.0°FDB (26.7°CDB) / 67.0°FWB (19.4°CWB)		70.0°FDB (21.1°CDB) / 60.0°FWB (15.6°CWB)		
	Outdoor	95.0°FDB (35.0°CDB) / 75.0°FWB (24.0°CWB)		47.0°FDB (8.3°CDB) / 43.0°FWB (6.1°CWB)		
	Piping Length	25 ft				
Drawing No.	3D159398A					
Note(s)	SL: The quiet fan level of the airflow rate setting. When indoor unit is connected with multi-system outdoor unit. Please refer to the specifications of the multi-system outdoor unit to be connected.					

Conversion Formulae
kcal/h = kW × 860
Btu/h = kW × 3412
cfm = m³/min × 35.3

Model	Indoor Unit		FVXV15AVJUW9		FVXV15AVJUT9	
	Outdoor Unit		RXP15AVJU9		RXP15AVJU9	
			Cooling	Heating	Cooling	Heating
Power Supply			1 ϕ, 208 - 230 V, 60 Hz		1 ϕ, 208 - 230 V, 60 Hz	
Capacity Rated (Min. - Max.)	Btu/h		15,000 (6,100 ~ 19,100)	18,000 (7,300 ~ 20,400)	15,000 (6,100 ~ 19,100)	18,000 (7,300 ~ 20,400)
Running Current (Rated)	A		6.46 - 5.48	7.89 - 7.14	6.46 - 5.48	7.89 - 7.14
Power Consumption (Rated)	W		1,250 - 1,250	1,628 - 1,628	1,250 - 1,250	1,628 - 1,628
Power Factor (Rated)	%		93.0 - 93.1	99.2 - 99.2	93.0 - 93.1	99.2 - 99.2
SEER2			19.5	—	19.5	—
HSPF2 (Region IV)			—	9.5	—	9.5
HSPF2 (Region V)			—	8.0	—	8.0
EER2 (Rated)	Btu/W-h		12.0	—	12.0	—
COP2 (°F (-15°C))	W/W		—	1.8	—	1.8
Piping Connections	Liquid	in. (mm)	ϕ1/4 (6.4)		ϕ1/4 (6.4)	
	Gas	in. (mm)	ϕ1/2 (12.7)		ϕ1/2 (12.7)	
	Drain	in. (mm)	ϕ13/16 (20)		ϕ13/16 (20)	
Heat Insulation			Both Liquid and Gas Pipes		Both Liquid and Gas Pipes	
Max. Interunit Piping Length	ft (m)		98-1/2 (30)		98-1/2 (30)	
Max. Interunit Height Difference	ft (m)		65-5/8 (20)		65-5/8 (20)	
Chargeless	ft (m)		49-1/4 (15)		49-1/4 (15)	
Amount of Additional Charge of Refrigerant	oz/ft (g/m)		0.22 (20)		0.22 (20)	
Indoor Unit		FVXV15AVJUW9		FVXV15AVJUT9		
Front Panel Color (Mancel No.)			White (N9.5)		Espresso (B-690)	
Heat Exchanger	Rows × Stages, Fin per Inch		2 × 22, 21		2 × 22, 21	
	Fin Spec / Tube		Multi Slit Fin / ϕ5 Hi-XB Tube		Multi Slit Fin / ϕ5 Hi-XB Tube	
Airflow Rate	H / M / L / SL	cfm	392 / 311 / 254 / 201	417 / 321 / 272 / 215	392 / 311 / 254 / 201	417 / 321 / 272 / 215
		m³/min	11.1 / 8.8 / 7.2 / 5.7	11.8 / 9.1 / 7.7 / 6.1	11.1 / 8.8 / 7.2 / 5.7	11.8 / 9.1 / 7.7 / 6.1
Air Direction Control			Right, Left, Upward, Downward		Right, Left, Upward, Downward	
Air Filter			Removable, Washable, Mildew Proof		Removable, Washable, Mildew Proof	
Fan Motor	H / M / L / SL	rpm	840 / 680 / 570 / 460	890 / 700 / 600 / 490	840 / 680 / 570 / 460	890 / 700 / 600 / 490
	Motor output	Hp	0.05		0.05	
Fan	Type		Sirocco Fan		Sirocco Fan	
Running Current (Rated)	A		0.17 - 0.15	0.20 - 0.18	0.17 - 0.15	0.20 - 0.18
Power Consumption (Rated)	W		19 - 19	22 - 22	19 - 19	22 - 22
Power Factor (Rated)	%		48.0 - 54.1	48.0 - 52.6	48.0 - 54.1	48.0 - 52.6
Temperature Control			Microcomputer Control		Microcomputer Control	
Dimensions (H × W × D)	in. (mm)		23-5/8 × 29-1/2 × 9-3/8 (600 × 750 × 238)		23-5/8 × 29-1/2 × 9-3/8 (600 × 750 × 238)	
Packaged Dimensions (H × W × D)	in. (mm)		29-13/16 × 34-7/16 × 13-5/8 (757 × 874 × 346)		29-13/16 × 34-7/16 × 13-5/8 (757 × 874 × 346)	
Weight (Mass)	lbs (kg)		40 (18)		40 (18)	
Gross Weight (Gross Mass)	lbs (kg)		50 (23)		50 (23)	
Sound Pressure Level (H / M / L / SL)	dB(A)		46 / 40 / 36 / 30	46 / 40 / 36 / 30	46 / 40 / 36 / 30	46 / 40 / 36 / 30
Remote Controller			ARC466A89		ARC466A89	
Outdoor Unit		RXP15AVJU9		RXP15AVJU9		
Casing Color			Ivory White		Ivory White	
Heat Exchanger	Fin Spec / Tube		Waffle Fin (PE) / ϕ7 Hi-XSL Tube		Waffle Fin (PE) / ϕ7 Hi-XSL Tube	
Fan Motor	Motor output	Hp	0.02		0.02	
Compressor	Type		Hermetically Sealed Swing Type		Hermetically Sealed Swing Type	
	Model		2Y260BPAX1A		2Y260BPAX1A	
Refrigerant Oil	Type		FW68DA		FW68DA	
	Charge	oz (L)	30.43 (0.90)		30.43 (0.90)	
Refrigerant	Type		R-32		R-32	
	Charge	lbs (kg)	3.04 (1.38)		3.04 (1.38)	
Airflow Rate	cfm (m³/min)		2,383 (67.5)	2,327 (65.9)	2,383 (67.5)	2,327 (65.9)
Fan	Type		Propeller		Propeller	
Running Current (Rated)	A		6.29 - 5.69	7.69 - 6.96	6.29 - 5.69	7.69 - 6.96
Power Consumption (Rated)	W		1,231 - 1,231	1,606 - 1,606	1,231 - 1,231	1,606 - 1,606
Power Factor (Rated)	%		94.1 - 94.1	99.9 - 99.9	94.1 - 94.1	99.9 - 99.9
Dimensions (H × W × D)	in. (mm)		29-1/2 × 34-1/4 × 12-5/8 (750 × 870 × 320)		29-1/2 × 34-1/4 × 12-5/8 (750 × 870 × 320)	
Packaged Dimensions (H × W × D)	in. (mm)		32-1/16 × 40-5/16 × 16 (814 × 1,024 × 406)		32-1/16 × 40-5/16 × 16 (814 × 1,024 × 406)	
Weight (Mass)	lbs (kg)		127 (58)		127 (58)	
Gross Weight (Gross Mass)	lbs (kg)		135 (61)		135 (61)	
Sound Pressure Level	dB(A)		55	57	55	57
Conditions Based on	Indoor		80.0°FDB (26.7°CDB) / 67.0°FWB (19.4°CWB)	70.0°FDB (21.1°CDB) / 60.0°FWB (15.6°CWB)	80.0°FDB (26.7°CDB) / 67.0°FWB (19.4°CWB)	70.0°FDB (21.1°CDB) / 60.0°FWB (15.6°CWB)
	Outdoor		95.0°FDB (35.0°CDB) / 75.0°FWB (24.0°CWB)	47.0°FDB (8.3°CDB) / 43.0°FWB (6.1°CWB)	95.0°FDB (35.0°CDB) / 75.0°FWB (24.0°CWB)	47.0°FDB (8.3°CDB) / 43.0°FWB (6.1°CWB)
	Piping Length		25 ft		25 ft	
Drawing No.			3D159399A			
Note(s)			SL: The quiet fan level of the airflow rate setting. When indoor unit is connected with multi-system outdoor unit. Please refer to the specifications of the multi-system outdoor unit to be connected.			

Conversion Formulae
kcal/h = kW × 860
Btu/h = kW × 3412
cfm = m³/min × 35.3

Model	Indoor Unit		FVXV18AVJUW9		FVXV18AVJUT9	
	Outdoor Unit		RXP18AVJU9		RXP18AVJU9	
			Cooling	Heating	Cooling	Heating
Power Supply	1 ϕ, 208 - 230 V, 60 Hz				1 ϕ, 208 - 230 V, 60 Hz	
Capacity Rated (Min. - Max.)	Btu/h	17,600 (6,200 ~ 21,400)	20,000 (8,300 ~ 21,800)	17,600 (6,200 ~ 21,400)	20,000 (8,300 ~ 21,800)	
Running Current (Rated)	A	7.51 - 6.79	8.36 - 7.56	7.51 - 6.79	8.36 - 7.56	
Power Consumption (Rated)	W	1,467 - 1,467	1,724 - 1,724	1,467 - 1,467	1,724 - 1,724	
Power Factor (Rated)	%	93.9 - 93.9	99.1 - 99.1	93.9 - 93.9	99.1 - 99.1	
SEER2		19.5	—	19.5	—	
HSPF2 (Region IV)		—	9.5	—	9.5	
HSPF2 (Region V)		—	7.9	—	7.9	
EER2 (Rated)	Btu/W-h	12.0	—	12.0	—	
COP2 (°F (-15°C))	W/W	—	1.8	—	1.8	
Piping Connections	Liquid	in. (mm)	ϕ1/4 (6.4)		ϕ1/4 (6.4)	
	Gas	in. (mm)	ϕ1/2 (12.7)		ϕ1/2 (12.7)	
	Drain	in. (mm)	ϕ13/16 (20)		ϕ13/16 (20)	
Heat Insulation	Both Liquid and Gas Pipes				Both Liquid and Gas Pipes	
Max. Interunit Piping Length	ft (m)	98-1/2 (30)		98-1/2 (30)		
Max. Interunit Height Difference	ft (m)	65-5/8 (20)		65-5/8 (20)		
Chargeless	ft (m)	49-1/4 (15)		49-1/4 (15)		
Amount of Additional Charge of Refrigerant	oz/ft (g/m)	0.22 (20)		0.22 (20)		
Indoor Unit		FVXV18AVJUW9		FVXV18AVJUT9		
Front Panel Color (Mancel No.)	White (N9.5)				Espresso (B-690)	
Heat Exchanger	Rows × Stages, Fin per Inch	2 × 22, 21				
	Fin Spec / Tube	Multi Slit Fin / ϕ5 Hi-XB Tube				
Airflow Rate	H / M / L / SL	cfm	448 / 332 / 286 / 240	455 / 360 / 290 / 240	448 / 332 / 286 / 240	455 / 360 / 290 / 240
		m³/min	12.7 / 9.4 / 8.1 / 6.8	12.9 / 10.2 / 8.2 / 6.8	12.7 / 9.4 / 8.1 / 6.8	12.9 / 10.2 / 8.2 / 6.8
Air Direction Control	Right, Left, Upward, Downward				Right, Left, Upward, Downward	
Air Filter	Removable, Washable, Mildew Proof				Removable, Washable, Mildew Proof	
Fan Motor	H / M / L / SL	rpm	950 / 720 / 630 / 540	970 / 780 / 640 / 540	950 / 720 / 630 / 540	970 / 780 / 640 / 540
	Motor output	Hp	0.05		0.05	
Fan	Type	Sirocco Fan				
Running Current (Rated)	A	0.23 - 0.21	0.25 - 0.23	0.23 - 0.21	0.25 - 0.23	
Power Consumption (Rated)	W	26 - 26	27 - 27	26 - 26	27 - 27	
Power Factor (Rated)	%	48.0 - 53.6	48.0 - 51.7	48.0 - 53.6	48.0 - 51.7	
Temperature Control	Microcomputer Control				Microcomputer Control	
Dimensions (H × W × D)	in. (mm)	23-5/8 × 29-1/2 × 9-3/8 (600 × 750 × 238)				
Packaged Dimensions (H × W × D)	in. (mm)	29-13/16 × 34-7/16 × 13-5/8 (757 × 874 × 346)				
Weight (Mass)	lbs (kg)	40 (18)				
Gross Weight (Gross Mass)	lbs (kg)	50 (23)				
Sound Pressure Level (H / M / L / SL)	dB(A)	49 / 42 / 38 / 34	49 / 43 / 37 / 33	49 / 42 / 38 / 34	49 / 43 / 37 / 33	
Remote Controller	ARC466A89				ARC466A89	
Outdoor Unit		RXP18AVJU9		RXP18AVJU9		
Casing Color	Ivory White				Ivory White	
Heat Exchanger	Fin Spec / Tube	Waffle Fin (PE) / ϕ7 Hi-XSL Tube				
Fan Motor	Motor output	Hp	0.02		0.02	
Compressor	Type	Hermetically Sealed Swing Type				
	Model	2Y260BPAX1A				
Refrigerant Oil	Type	FW68DA				
	Charge	oz (L)	30.43 (0.90)		30.43 (0.90)	
Refrigerant	Type	R-32				
	Charge	lbs (kg)	3.04 (1.38)		3.04 (1.38)	
Airflow Rate	cfm (m³/min)	2,383 (67.5)	2,327 (65.9)	2,383 (67.5)	2,327 (65.9)	
Fan	Type	Propeller				
Running Current (Rated)	A	7.28 - 6.58	8.11 - 7.33	7.28 - 6.58	8.11 - 7.33	
Power Consumption (Rated)	W	1,441 - 1,441	1,697 - 1,697	1,441 - 1,441	1,697 - 1,697	
Power Factor (Rated)	%	95.2 - 95.2	99.9 - 99.9	95.2 - 95.2	99.9 - 99.9	
Dimensions (H × W × D)	in. (mm)	29-1/2 × 34-1/4 × 12-5/8 (750 × 870 × 320)				
Packaged Dimensions (H × W × D)	in. (mm)	32-1/16 × 40-5/16 × 16 (814 × 1,024 × 406)				
Weight (Mass)	lbs (kg)	127 (58)				
Gross Weight (Gross Mass)	lbs (kg)	135 (61)				
Sound Pressure Level	dB(A)	55	57	55	57	
Conditions Based on	Indoor	80.0°FDB (26.7°CDB) / 67.0°FWB (19.4°CWB)		80.0°FDB (26.7°CDB) / 67.0°FWB (19.4°CWB)		
	Outdoor	95.0°FDB (35.0°CDB) / 75.0°FWB (24.0°CWB)		95.0°FDB (35.0°CDB) / 75.0°FWB (24.0°CWB)		
	Piping Length	25 ft				
Drawing No.	3D159400A					
Note(s)	SL: The quiet fan level of the airflow rate setting. When indoor unit is connected with multi-system outdoor unit. Please refer to the specifications of the multi-system outdoor unit to be connected.					

Conversion Formulae
kcal/h = kW × 860
Btu/h = kW × 3412
cfm = m³/min × 35.3