

Product Description

OBEX CORTEX 0272FR UltraBoard Jointing Tape is a high-performance jointing tape developed for sealing the joints of the 0271FR UltraBoard System. The acrylic dispersion adhesive maintains a high-performance during exposure to heat, cold, water and moisture. The UltraBoard Jointing Tape contributed to a 2400pa watertightness of the UltraBoard system.

Product Specifications

Widths	150mm
Lengths	25m
Thickness	0.3mm
Colour	Black

Key features

- » 12 months UV exposure
- » Very high bond strength
- » Achieves over 2400pa watertightness when installed
- » No joint sealant required between boards

Technical Data

Adhesive carrier	Woven glass fibre
Adhesive system	FR acrylic dispersion
Release liner	Silicone coated PE liner, White
Temperature Resistance	-40°C – +120°C
Recommended installation temperature	+5°C – 40°C
Tack	Excellent
UV Exposure	12 Months

Product Applications

- » Sealing joints of OBEX CORTEX 0271FR UltraBoard

Packaging & Storage

- » Packaging: 8 rolls per box
- » Conditions – store in a dry location, protected from prolonged exposure to moisture
- » Shelf life – 12 months
- » Temperatures – 10-30°C

Associated Products

- » OBEX CORTEX 0271FR UltraBoard
- » OBEX CORTEX 0290FR Self-Drilling Screws
- » OBEX CORTEX 0280FR Board Sealant
- » OBEX CORTEX 0273FR UltraBoard Patches

Important Notes

- » The 0272FR UltraBoard Jointing Tape has been specifically designed and developed for use with the 0271FR UltraBoard system. Any other application shall be checked and reviewed by OBEX.

Related Documents

- » Installation Guide
- » Safety Data Sheet