FIRECHIEF XTR WET CHEMICAL **EXTINGUISHERS**



MODEL:

FXWC2 FXWC3 FXWC6

- Kitemark and LPCB approved to BS EN3
- MED approved
- Approved to 35kV dielectric test
- 5 year guarantee
- High performance rating including A, B and F fires
- Supplied complete with bracket
- Corrosion resistant finish
- Internal polyethylene lining
- Squeeze grip operation

EXTRA PERFORMANCE A,B&F **RATING**



FXWC2 100-1212



ET CHEMICAL

FIRECHIEF



WET CHEMICAL FIRE EXTINGUISHER























+44 (0) 330 999 0019



sales@firechiefglobal.com



firechiefglobal.com

FIRECHIEF XTR **WET CHEMICAL EXTINGUISHERS**

Ideal for F class fires involving cooking oils and fats, the wet chemical extinguishant rapidly puts flam es out, cools the burning oil and seals the surface, preventing reignition and rise of the fire spreading.



making the world a safer place

MODEL:









Specifications

Model	FXWC2	FXWC3	FXWC6
Product Code	100-1212	100-1214	100-1216
Description	Firechief XTR 2L Wet Chemical Extinguisher	Firechief XTR 3L Wet Chemical Extinguisher	Firechief XTR 6L Wet Chemical Extinguisher
Capacity (I)	2	3	6
Fire Rating	8A 34B 25F	13A 70B 40F	21A 113B 75F
MED Approval	YES	YES	YES
Throw Range (m)	3	3	5
Discharge Time (secs)	12	15	40
Working Pressure (bar)	9	9	9
Temperature Range (°C)	(5°-+60°)	(5°-+60°)	(5°-+60°)
Product Height (mm)	405	435	531
Product Diameter (mm)	110	130	162
Filled Weight (kg)*	3.6	5.2	9.25
Carton Height (mm)	440	460	555
Carton Length (mm)	125	145	180
Carton Width (mm)	125	145	170
Packaged Weight (kg)**	3.9	5.6	10
Product EAN	5055377901530	5055377900885	5055377900151

^{*} Extinguisher, contents and plastic base only (where applicable) - not including hose, bracket or packaging.

For more information contact: Firechief Global, 3 Lands End Way, Oakham, Rutland, UK, LE15 6RB | Imported into EU by: Sentura Group (Ireland) Ltd, Joyce House, 21-23 Holles Street, Dublin 2, Ireland







^{**} Includes all packaging, hose / horn and bracket.