

## Product data sheet


## Premier

## AR910



ARRONE mortice sashlock case:

- Function: Latch bolt and deadbolt operation
- Deadbolt projection: 21 mm, single throw
- Forend/strike material: Stainless steel
- Forend type: Single
- CE Marked: AG0067, UKCA Marked: AG7668
  - **BS EN 12209**: 3 | X | 8 | 1\* | 0 | G | 4 | B | A | 3 | 0
- Certifire approved: CF530, CE DOP: HUK0007, UKCA DOP: HUK007-UK
- Testing: **BS EN 1634-1**. Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minutes steel fire doors.
- Meets dimensional recommendations of **BS 8300** and ADM for locks
- \* The AR910 series lock case has been successfully fire tested with the use of an
  intumescent kit. The supply and fitting of this intumescent kit is essential to the products
  compliance with the fire test and CE marking evidence it has gained. HOPPE takes no
  responsibility for any locks purchased and fitted without sufficient intumescent protection.



Article number	87107855
Product ref.	AR910-S-60-PBR
EAN-Code	5051358034419
Country of origin	Portugal
CN-Code	83014019
Operation	Lever/Lever Handle Set
Follower	8 mm
Backset	60 mm, pierced for furniture and es- cutcheons at 38 mm centres
(Key)Hole size	Euro profile cylinder
Key hole distance	72 mm
Door type	
Door type	wooden door
Fixings	wooden door Timber door
Fixings	
Fixings Keying	Timber door
Fixings Keying Corner	Timber door square corner
Fixings Keying Corner Shape	Timber door square corner square F77 brass-coloured,
Fixings Keying Corner Shape Finish	Timber door  square corner square F77 brass-coloured, polished F77 brass-coloured,
Fixings Keying Corner Shape Finish Face plate finish	Timber door  square corner square F77 brass-coloured, polished F77 brass-coloured, polished