

Premier

Product data sheet


AR910

| | Article number | 87117078 |
|---|-------------------|--|
| | Product ref. | AR910-R-80-SSS |
| | EAN-Code | 5051358061187 |
| | Country of origin | Portugal |
| | CN-Code | 83014019 |
| | Operation | Lever/Lever Handle Set |
| | Follower | 8 mm |
| | Backset | 80 mm, pierced for furniture and es- cutcheons at 38 mm centres |
| | (Key)Hole size | Euro profile cylinder |
| | Key hole distance | 72 mm |
| | Door type | wooden door |
| | Fixings | Timber door |
| | Keying | |
| | Corner | radius corners |
| RRONE mortice sashlock case: Function: Latch bolt and deadbolt operation | Shape | radiused |
| | Finish | F69 satin stainless steel |
| Deadbolt projection: 21 mm, single throw | Face plate finish | F69 satin stainless |
| Forend/strike material: Stainless steel | | steel |
| Forend type: Single CE Marked: AG0067, UKCA Marked: AG7668 BS EN 12209: 3 X 8 1* 0 G 4 B A 3 0 | Range | ARRONE Range |
| | Packing unit | 1 |
| | Outer carton | 25 |
| Certifire approved: CF530, CE DOP: HUK0007, UKCA DOP: HUK007-UK Testing: BS EN 1634-1 . Assessed for use on 30, 60, 90 and 120 minute timber fire doors | | |
| | | |

AR

- F

- (
- and 240 minutes steel fire doors.
- Meets dimensional recommendations of **BS 8300** and ADM for locks
- * The AR910 series lock case has been successfully fire tested with the use of an intumescent kit. The supply and fitting of this intumescent kit is essential to the products compliance with the fire test and CE marking evidence it has gained. HOPPE takes no responsibility for any locks purchased and fitted without sufficient intumescent protection.



HOPPE (UK) · Ltd Gailey Park · Gravelly Way · Standeford · Wolverhampton WV10 7GW

Tel. 01902 484 400 · Tel. Sales Direct: 01902 484 410/20 · Fax 01902 484 406 · Fax Sales Direct: 01902 484 417/27 · info.uk@hoppe.com · www.hoppe.com