

Product data sheet


Plus

AR8100



ARRONE mortice sashlock case:

- Function: Latch bolt and deadbolt operation
- Deadbolt Projection: 21 mm, double throw
- Forend/strike material: Stainless steel
- Forend type: Double
- CE Marked: AG0087, UKCA Marked: AG7670
 - **BS EN 12209**: 3 | M | 8 | 1* | 0 | G | 3 | B | C | 2 | 0
- Certifire approved: CF5022, CE DOP: HUK0030, UKCA DOP: HUK0030-UK
- Testing: **BS EN 1634-1**. Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minutes steel fire doors.
- Meets dimensional recommendations of BS 8300 and ADM for locks
- * The AR8100 series lock case has been successfully fire tested with the use of an
 intumescent kit. The supply and fitting of this intumescent kit is essential to the products
 compliance with the fire test and CE marking evidence it has gained. HOPPE takes no
 responsibility for any locks purchased and fitted without sufficient intumescent protection.



R8100-S-60-SSS
51358066021
ortugal
8014019
ever/Lever Handle et
mm
omm, pierced for miture and es- atcheons at 38 mm entres
ıro profile cylinder
2 mm
uare corner
uare
69 satin stainless eel
69 satin stainless eel
RRONE Range