

Product data sheet

Premier

AR6409



ARRONE overhead door closing device:

- Power size: 2 to 4 adjustable by spring tension
- Function: Closing, latching, backcheck
- Cover: Slimline cover
- Maximum door width: 1,100 mm
- Maximum door weight: 80 kg
- Arm application: door mount pull, transom mount push
- Successfully type tested for conformity to all the requirements of **BS EN 1154:1997**
 - Door mount pull side: 4 | 8 | 4/2 | 1* | 1 | 3
 - Transom mount push side: 3 | 8 | 4/2 | 1* | 1 | 3
- Included in a successful fire test to **BS EN 1634** Part 1. Assessed for use on 30, 60 and 120 minutes timber fire doors.
- CE Marked: AD5284, UKCA Marked: AD7689
- Certifire approved: CF5430; CE DOP: HUK0065, UKCA DOP: HUK0065-UK

Article number	50008407
Product ref.	AR6409B-L-SE
EAN-Code	5051358084506
Country of origin	Taiwan
CN-Code	83026000
Door type	wooden door
Maximum door width	1100 mm
Maximum door weight	80 kg
Arm Application	door mount pull, transom mount push
Mechanism function	Backcheck, adjustable power, closing/latching speed
Mechanism type	cam action
Fixings	Timber door
Slide track application	door mount pull, transom mount push
Shape	Slimline
Power size	2 to 4
Opening Angle	max. 180° opening
Mechanism dimensions and fixing centres	240x56x43mm; centres 100x41mm
Arm type	Surface slide arm
Finish	Silver Enamel
Finish of the cover	Silver Enamel
Range	ARRONE Range
Packing unit	1
Outer carton	4

