

## Product data sheet

### Premier

AR6509



ARRONE overhead door closing device:

- Power size: 2 to 5 adjustable by spring tension
- Function: Closing, latching, backcheck, delayed action
- Cover: Slimline cover
- Maximum door width: 1,250 mm
- Maximum door weight: 100 kg
- Arm application: door mount pull, transom mount push
- Successfully type tested for conformity to all the requirements of **BS EN 1154:1997**
  - Door mount pull side: 4 | 8 | 5/2 | 1\* | 1 | 3
  - Transom mount push side: 3 | 8 | 5/2 | 1\* | 1 | 3
- Included in a successful fire test to **BS EN 1634** Part 1. Assessed for use on 30, 60 and 120 minutes timber fire doors.
- CE Marked: AD5284, UKCA Marked: AD7690
- Certifire approved: CF5430, CE DOP: HUK0066, UKCA DOP: HUK0066-UK

|                                         |                                                                      |
|-----------------------------------------|----------------------------------------------------------------------|
| Article number                          | 50008468                                                             |
| Product ref.                            | AR6509B-L-SE                                                         |
| EAN-Code                                | 5051358084582                                                        |
| Country of origin                       | Taiwan                                                               |
| CN-Code                                 | 83026000                                                             |
| Door type                               | wooden door                                                          |
| Maximum door width                      | 1250 mm                                                              |
| Maximum door weight                     | 100 kg                                                               |
| Arm Application                         | door mount pull, transom mount push                                  |
| Mechanism function                      | Backcheck, delayed action, spring adjustment, closing/latching speed |
| Mechanism type                          | cam action                                                           |
| Fixings                                 | Timber door                                                          |
| Slide track application                 | door mount pull, transom mount push                                  |
| Shape                                   | Slimline                                                             |
| Power size                              | 2 to 5                                                               |
| Opening Angle                           | max. 180° opening                                                    |
| Mechanism dimensions and fixing centres | 256.5x60x48mm; centres 112x45mm                                      |
| Arm type                                | Surface slide arm                                                    |
| Finish                                  | Silver Enamel                                                        |
| Finish of the cover                     | Silver Enamel                                                        |
| Range                                   | ARRONE Range                                                         |
| Packing unit                            | 1                                                                    |
| Outer carton                            | 4                                                                    |

