

Product data sheet


Plus

AR8780



ARRONE lift off hinge:

- Material: Stainless Steel
- Hinge Grade: Grade 13
- Shape: Radius
- Bearing/Washer: Phosphor bronze (maintenance free)
- Unit of measure (pack size): Sold as singles
- Handed (Please specify desired hand on ordering)
- Door weight: Suitable for doors weighing up to 120 kg
- Fixing: 20 x stainless steel pozidrive countersunk wood screws
- Testing: **BS EN 1935** (Classification: 4 | 7 | 6 | 1* | 1 | 4 | 0 | 13)
- CE Marked: AC5050, UKCA Marked: AC7677
- Certifire approved: CF5534, CE DOP: HUK0063, UKCA DOP: HUK0063-UK
- BS EN 1634 Part 1. Assessed for use on 30 and 60 minutes timber fire doors
- * The AR8782 series hinge range has been successfully fire tested with the use of an
 intumescent kit. The supply and fitting of this intumescent kit is essential to the products
 compliance with the fire test, CE marking and CERTIFIRE evidence it has gained. HOPPE
 takes no responsibility for any hinges purchased and fitted without matching and sufficient
 intumescent protection.



Article number	50009625
Product ref.	AR8782-LH-SSS-A1
EAN-Code	5051358085756
Country of origin	China
CN-Code	83021000
Dimension	100x88 mm
Door type	wooden door
Fixings	Timber door
Shape	
Leaf corner	radius corners
Drill	5 holes ANSI tem-
	plate drilled, counter-
	sunk
Material thickness	3 mm
Finish	Satin Stainless Steel
Range	ARRONE Range
Packing unit	1
. c.c g c.i	ı