

Product data sheet


Premier


AR912



ARRONE mortice deadlock case:

- Function: Deadbolt operation
- Deadbolt projection: 21 mm, single throw
- Forend/strike material: Stainless steel
- Forend type: Single
- CE Marked: AG0068, UKCA Marked: AG7669
- Certifire approved: CF530, CE DOP: HUK0008, UKCA DOP: HUK0008-UK
 - **BS EN 12209**: 3 | X | 8 | 1* | 0 | G | 4 | B | A | 0 | 0
- Testing: **BS EN 1634-1**. Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minute steel fire doors.
- Meets dimensional recommendations of **BS 8300** and ADM for locks
- * The AR912 series lock case has been successfully fire tested with the use of an
 intumescent kit. The supply and fitting of this intumescent kit is essential to the products
 compliance with the fire test and CE marking evidence it has gained. HOPPE takes no
 responsibility for any locks purchased and fitted without sufficient intumescent protection.





| Article number | 87107865 |
|-------------------|-----------------------|
| Product ref. | AR912-S-60-SSS |
| EAN-Code | 5051358034600 |
| Country of origin | Portugal |
| CN-Code | 83014019 |
| Follower | 8 mm |
| Backset | 60 mm, pierced for |
| | escutcheons at 38 |
| | mm centres |
| (Key)Hole size | Euro profile cylinder |
| Key hole distance | 72 mm |
| Door type | wooden door |
| Fixings | Timber door |
| Keying | |
| Corner | square corner |
| Shape | square |
| Finish | Satin Stainless Steel |
| Face plate finish | F69 satin stainless |
| | steel |
| Range | ARRONE Range |
| Packing unit | 1 |
| Outer carton | 25 |