

## Product data sheet


## Premier

## AR912



ARRONE mortice deadlock case:

- Function: Deadbolt operation
- Deadbolt projection: 21 mm, single throw
- Forend/strike material: Stainless steel
- Forend type: Single
- CE Marked: AG0068, UKCA Marked: AG7669
- $\bullet\,$  Certifire approved: CF530, CE DOP: HUK0008, UKCA DOP: HUK0008-UK
  - **BS EN 12209**: 3 | X | 8 | 1\* | 0 | G | 4 | B | A | 0 | 0
- Testing: **BS EN 1634-1**. Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minute steel fire doors.
- Meets dimensional recommendations of **BS 8300** and ADM for locks
- \* The AR912 series lock case has been successfully fire tested with the use of an
  intumescent kit. The supply and fitting of this intumescent kit is essential to the products
  compliance with the fire test and CE marking evidence it has gained. HOPPE takes no
  responsibility for any locks purchased and fitted without sufficient intumescent protection.



Article number	50001711
Product ref.	AR912-S-80-SSS
EAN-Code	5051358076617
Country of origin	Portugal
CN-Code	83014019
Follower	8 mm
Backset	80 mm, pierced for
	escutcheons at 38
	mm centres
(Key)Hole size	Euro profile cylinder
Key hole distance	72 mm
Door type	wooden door
Fixings	Timber door
Keying	
Corner	square corner
Shape	square
Finish	Satin Stainless Steel
Face plate finish	F69 satin stainless
	steel
Range	ARRONE Range
Packing unit	1
Outer carton	25