

Product data sheet

Premier

AR914



Article number	87107880
Product ref.	AR914-R-60-SSS
EAN-Code	5051358054851
Country of origin	Portugal
CN-Code	83014019
Operation	Lever/Lever Handle Set
Follower	8 mm
Backset	60 mm, pierced for furniture and es-cutcheons at 38 mm centres
(Key)Hole size	Euro profile cylinder
Key hole distance	72 mm
Door type	wooden door
Fixings	Timber door
Corner	radius corners
Shape	radiused
Finish	Satin Stainless Steel
Face plate finish	F69 satin stainless steel
Range	ARRONE Range
Packing unit	1
Outer carton	25

ARRONE mortice nightlatch case:

- Function: Latch bolt with anti thrust operation
- Forend/strike material: Stainless steel
- Forend type: Single
- CE Marked: ABB010, AG0067, UKCA Marked: ABB7653, AG7668
 - **BS EN 12209:** 3 | X | 8 | 1* | 0 | G | - | B | 0 | 3 | 0
 - **BS EN 179:** 3 | 7 | 6 | B | 1 | 4 | 4 | 1 | A | B
 - **BS EN 179:** 3 | 7 | 6 | B | 1 | 4 | 4 | 1 | A | D
- Certifire approved: CF530, CE DOP: HUK0011 and HUK0052, UKCA DOP: HUK001-UK and HUK0052-UK
- Testing: **BS EN 1634-1.** Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minutes steel fire doors.
- **To comply with BS EN 179 certification, only lever handles and associated fixings included in the test evidence must be used.**
- Meets dimensional recommendations of **BS 8300** and ADM for locks
- * The AR914 series lock case has been successfully fire tested with the use of an intumescent kit. The supply and fitting of this intumescent kit is essential to the products compliance with the fire test and CE marking evidence it has gained. HOPPE takes no responsibility for any locks purchased and fitted without sufficient intumescent protection.

