

Safety Data Sheet according to Regulation (EC) No. 2020/878

SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product Identifier 8677 Revision Date: 13/06/2023

Product Name: CARBOCRYLIC 1295 HS PART A

/ CARBOCRYLIC 1295 HS

CARBO-KIT PART A

Version Number: 3

22/12/2022

Supercedes Date:

UFI Code: NXR2-X0GG-K00E-YAM1

Nano Form:

1.2 Relevant identified uses of the

substance or mixture and uses

advised against

Base component of 2 components coating - Industrial use.

Advised against: others than recommended

Product to be mixed with:

Mixing ratio by volume Part A/

Part B:

CARBOCRYLIC 1295 HS PART B / CARBOCRYLIC 1295 HS CARBO-KIT PART B

7:1

1.3 Details of the supplier of the safety data sheet

Manufacturer: Carboline Norge AS

Postboks 593 3412 Lierstranda

Norway

Regulatory / Technical Information:

+47 32 85 73 00 +47 32 85 74 00

Datasheet Produced by: Tarka, Malgorzata - hms@carboline.com

1.4 Emergency telephone number: CHEMTREC +1 703 5273887 (Outside US)

SECTION 2: Hazards Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

Flammable Liquid, category 3

Skin Irritation, category 2

Skin Sensitizer, category 1

H317

Serious Eye Damage, category 1 H318
STOT, repeated exposure, category 2 H373
Hazardous to the aquatic environment, Chronic, category 3

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

Butan-1-ol, 2-methylpropan-1-ol, ethylbenzene, xylene, Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

HAZARD STATEMENTS

Other EU extensions	EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Serious Eye Damage, category 1	H318	Causes serious eye damage.
STOT, repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment, Chronic, category 3	H412	Harmful to aquatic life with long lasting effects.
PRECAUTION PHRASES		
	P260	Do not breathe dust/fume/gas/mist/vapours/spray.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
	P308+313	IF exposed or concerned: Get medical advice/attention
	P332+313	If skin irritation occurs: Get medical advice/attention.
ADDITIONAL INFORMATION		
	ADD-04	Due to the viscosity, this product does not present an aspiration hazard.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.

Endocrine disrupting properties - Toxicity

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

Endocrine disrupting properties - Ecotoxicity

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

SECTION 3: Composition/Information On Ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Hazardous ingredients

Name According to EEC EINECS No. CAS-No. REACH Reg No.	<u>%</u>	Classifications	SCL Value ATE Value M-Factor	
titanium dioxide 236-675-5 13463-67-7	10 - <25		SCL:	-
01-2119489379-17			ATE:	-
			M-Factor:	-
xylene 215-535-7 1330-20-7 01-2119488216-32	10 - <25	H226-304-312-315-319-332-335-373-412 Acute Tox. 4 Dermal, Acute Tox. 4 Inhalation, Aquatic Chronic 3, Asp. Tox. 1, Eye Irrit. 2, Flam. Liq. 3, Skin Irrit. 2, STOT RE 2, STOT SE 3 RTI	SCL:	-
01-2113-00210-02			ATE:	-
			M-Factor:	-
n-butyl acetate 204-658-1 123-86-4 01-2119485493-29	2.5 - <10	H226-336 Flam. Liq. 3, Skin Cracking, STOT SE 3 NE	SCL:	-
01 2110 100 100 20			ATE:	-
			M-Factor:	-
Butan-1-ol 200-751-6 71-36-3	2.5 - <10	H226-302-315-318-335-336 Acute Tox. 4 Oral, Eye Dam. 1, Flam. Liq. 3, Skin Irrit. 2, STOT SE 3 NE, STOT SE 3 RTI	SCL:	-
01-2119484630-38			ATE:	-
			M-Factor:	-

Date Pfiffled. 13/06/2023				Product. 6677
ethylbenzene 202-849-4 100-41-4	2.5 - <10	H225-304-332-373-412 Acute Tox. 4 Inhalation, Aquatic Chronic 3, Asp. Tox. 1, Flam. Liq. 2, STOT RE 2	SCL:	-
01-2119489370-35			ATE:	-
			M-Factor:	-
hydrocarbons, c9, aromatics 918-668-5 - 01-2119455851-35	1.0 - <2.5	H226-304-335-336-411 Aquatic Chronic 2, Asp. Tox. 1, Flam. Liq. 3, Skin Cracking, STOT SE 3 NE, STOT SE 3 RTI	SCL:	-
01-2119455651-55			ATE:	-
			M-Factor:	-
Siloxanes and Silicones, di-Me, reaction products with silica 614-122-2	1.0 - <2.5		SCL:	-
67762-90-7			ATE:	-
			M-Factor:	-
2-methylpropan-1-ol 201-148-0 78-83-1	1.0 - <2.5	H226-315-318-332-335-336 Acute Tox. 4 Inhalation, Eye Dam. 1, Flam. Liq. 3, Skin Irrit. 2, STOT SE 3 NE, STOT SE 3 RTI	SCL:	-
01-2119484609-23			ATE:	-
			M-Factor:	-
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate 915-687-0	0.1 - <1.0	H317-361F-400-410 Aquatic Acute 1, Aquatic Chronic 1, Repr. 2, Skin Sens. 1A	SCL:	-
1065336-91-5 01-2119491304-40			ATE:	-
			M-Factor:	-

Remarks:

CAS No 13463-67-7: Note 10
CAS numbers 41556-26-7 and 82919-37-7 are registered in REACH with REACH No. 01-2119491304-40, CAS number 1065336-91-5, and EC number 915-687-0.

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

SECTION 4: First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: Show this safety data sheet to the doctor in attendance.

AFTER INHALATION: Move to fresh air. Give oxygen or artificial respiration if needed. When risk of unconsciousness, place and transport the victim in secured recovery position. Provide fresh air, rest and warmth. Call a physician immediately.

AFTER SKIN CONTACT: Use a mild soap if available. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Do not use solvent or thinners to clean skin.

AFTER EYE CONTACT: Immediate medical attention is required. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously: Keep head below hips to prevent aspiration of stomach vomit into lungs. Provide fresh air, rest and warmth.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to skin. May cause sensitization by skin contact. Danger of serious damage to health by prolonged exposure. Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

SECTION 5: Firefighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above. Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

Heating or fire conditions liberates toxic gas. Flash back possible over considerable distance. As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Vapours may form explosive mixtures with air. Solvent vapours are heavier than air and may spread along floors and ignite.

5.3 Advice for firefighters

Fire will produce dense black smoke containing hazardous combustion products (see section 10). In the event of fire, wear self-contained breathing apparatus. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Keep containers and surroundings cool with water spray.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.1.2 For emergency responders

See Section 7, 8 and 10 for further information.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be

advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Do not let product enter drains. Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Clean with detergents. Avoid solvents.

6.4 Reference to other sections

Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. Provide sufficient air exchange and/or exhaust in work rooms. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is being used.

Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid heat, sparks, flames and other ignition sources.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Keep container closed. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Store in upright position only. Storage of flammable liquids. Store away from: oxidising materials, acids, and alkalis.

7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (UK WELS)

<u>Name</u>	CAS-No.	LTEL ppm	STEL ppm	STEL mg/m3	LTEL mg/m3
titanium dioxide	13463-67-7			10 (total dust)	4 (resp. dust)
xylene	1330-20-7	50	100	441	220
n-butyl acetate	123-86-4	150	200	966	724
Butan-1-ol	71-36-3		50	154	
ethylbenzene	100-41-4	100	125	552	441
hydrocarbons, c9, aromatics	-				551
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7			6 (Inh. dust)	2.4 (Resp. dust)
2-methylpropan-1-ol	78-83-1	50	75	231	154
Reaction mass of bis(1,2,2,6,6-pentamethyl-4 piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	- 1065336-91-5				

CAS-No. **OEL Note Name** 13463-67-7 titanium dioxide Sk 1330-20-7 xylene n-butyl acetate 123-86-4 Sk Butan-1-ol 71-36-3 100-41-4 Sk ethylbenzene

hydrocarbons, c9, aromatics

Siloxanes and Silicones, di-Me, reaction

products with silica

67762-90-7

2-methylpropan-1-ol

78-83-1

Reaction mass of bis(1,2,2,6,6-pentamethyl-4- 1065336-91-5

piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation. Annotations: Carc = Capable of causing cancer and/or heritable genetic damage, Sen = Capable of causing occupational asthma, Sk = Can be absorbed through the skin.

Chemical Name:

titanium dioxide

EC No.: CAS-No.: 236-675-5 13463-67-7

DNELs - Derived no effect level

	Workers			Consumers				
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required					10 mg/m³	700 mg/kg/ bw/	
Inhalation	10 mg/m³			_			day	
Dermal		_						

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.127 mg/L
Fresh water sediments	1000 mg/kg dw
Marine water	1 mg/L
Marine sediments	100 mg/kg dw
Food chain	1667 mg/kg (oral)
Microorganisms in sewage treatment	100 mg/kg
soil (agricultural)	100 mg/kg dw
Air	

Chemical Name:

xylene

EC No.: CAS-No.: 215-535-7 1330-20-7

DNELs - Derived no effect level

	Workers					Con	sumers	
Route of Exposure	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required			174 mg/m ³	174 mg/m³		1.6 mg/kg bw/	
Inhalation	289 mg/m ³	289 mg/m ³	77 mg/m ³	77 mg/m³			_	day
Dermal				180 mg/kg bw/				14.8 mg/m ³
				day				108 mg/kg bw/
								dav

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.327 mg/L
Fresh water sediments	12.46 mg/kg
Marine water	0.327 mg/L
Marine sediments	12.46 mg/kg
Food chain	
Microorganisms in sewage treatment	6.58 mg/L
soil (agricultural)	2.31 mg/kg
Air	

Chemical Name:

n-butyl acetate

EC No.: CAS-No.: 204-658-1 123-86-4

DNELs - Derived no effect level

		Wo	rkers			Con	sumers	
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral		Not	required		300 mg/m ³	2 mg/kg bw/	35.7 mg/m ³	2 mg/kg bw/day
Inhalation	600 mg/m ³	600 mg/m ³	300 mg/m ³	300 mg/m ³	(irritation	day -	(irritation	neurotoxicity-
	(irritation	11 mg/kg bw/		11 mg/kg bw/day	(respiratory	neurotoxicity-	(respiratory	35.7 mg/m ³
	(respiratory	day -			tract))	300 mg/m ³	tract))	6 mg/kg bw/day
	tract))	neurotoxicity-			No hazard	(irritation		
Dermal					identified	(respiratory		
						tract))		
						6 mg/kg bw/		
						day -		
						neurotoxicity		

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.18 mg/L
Fresh water sediments	0.981 mg/kg dw
Marine water	0.018 mg/L
Marine sediments	0.098 mg/kg dw
Food chain	
Microorganisms in sewage treatment	35.6 mg/L
soil (agricultural)	0.09 mg/kg
Air	

Chemical Name:

Butan-1-ol

EC No.: CAS-No.: 200-751-6 71-36-3

DNELs - Derived no effect level

	Workers			Consumers				
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required					115 mg/m3	1.562 mg/kg bw/	
Inhalation			310 mg/m3		_			day
Dermal		_						55.357 mg/m3
								3.125 mg/kg bw/
								day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0,082 mg/l
Fresh water sediments	0,178 mg/kg dw
Marine water	0,0082 mg/l
Marine sediments	0,0178 mg/kg dw
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	0,015 mg/kg dw
Air	

Chemical Name:

ethylbenzene

EC No.: CAS-No.: 202-849-4 100-41-4

DNELs - Derived no effect level

		Workers			Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral		Not	required					1.6 mg/kg bw/
Inhalation	293 mg/m3			77 mg/m3				day
Dermal		_		180 mg/kg bw/				15 mg/m3
				dav				

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.1 mg/L
Fresh water sediments	13.7 mg/kg
Marine water	0.01 mg/L
Marine sediments	1.37 mg/kg
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	2.68 mg/kg
Air	

Chemical Name:

hydrocarbons, c9, aromatics

EC No.: 918-668-5

DNELs - Derived no effect level

		Wo	rkers		Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral		Not required			640 m/m3	1152 mg/m3	178.57 mg/m3	_
Inhalation	1066.67 mg/	1286.4 mg/m3	837.5 mg/m3				-	
	m3			_				
Dermal		_						

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	
Fresh water sediments	
Marine water	
Marine sediments	
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	
Air	

Chemical Name:

2-methylpropan-1-ol

EC No.: CAS-No.: 201-148-0 78-83-1

DNELs - Derived no effect level

	Workers				Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral		Not required					55 mg/m3	25 mg/kg
Inhalation			310 mg/m3		_			
Dermal		_		_				

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0,4 mg/l
Fresh water sediments	1,56 mg/kg
Marine water	0,04 mg/l
Marine sediments	0,156 mg/kg
Food chain	
Microorganisms in sewage treatment	10 mg/l
soil (agricultural)	0,0756 mg/kg
Air	

Chemical Name:

Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

EC No.: CAS-No.: 915-687-0 1065336-91-5

DNELs - Derived no effect level

	Workers			Consumers				
Route of Exposure	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral		Not required						0.18 mg/kg bw/
Inhalation				1.27 mg/m3				day
Dermal		_		1.8 mg/kg bw/				0.31 mg/m3
				day				0.9 mg/kg bw/
					_			day

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.0022 mg/l
Fresh water sediments	
Marine water	0.00022 mg/l
Marine sediments	
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	
Air	

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Wear respiratory protection with combination filter (dust and gas filter, EN 14387:2004 +A1:2008) during spraying operations: Gas filter type A2 (organic substances). Dust filter P3 (for fine dust). When working in confined or poorly ventilated spaces, a battery powered assisted air-fed mask must be used.

EYE PROTECTION: Safety glasses with side-shields conforming to EN166.

HAND PROTECTION: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). Long sleeved clothing. Remove and wash contaminated clothing before re-use. Use chemical resistant gloves and lotions and barrier creams to prevent drying of the skin. Protective gloves complying with EN 374: Nitrile rubber. Viton®. Recommended glove material for mixed product: Protective gloves complying with EN 374: Butyl rubber. Nitril rubber.

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location. **ENGINEERING CONTROLS:** Ensure adequate ventilation, especially in confined areas.

SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Colour Misc. colours

Physical State LIQUID Odor Solvent

Odor threshold Not determined Not determined Melting point / freezing point (°C) Not determined Boiling point or initial boiling point and

boiling range (°C)

106 - 200

Flash Point, (°C) 26

Evaporation rate Not determined Flammability (solid, gas) Not determined

Lower and upper explosive limit 0.7 - 10.9

Vapour Pressure Not determined Relative vapour density Not determined Density and/or relative density 1.32 - 1.42 Solubility in / Miscibility with water Insoluble

Partition coefficient: n-octanol/water Not determined

Auto-ignition temperature (°C) 400

Decomposition temperature (°C) Not determined

Kinematic viscosity 95 - 105 / > 20.5 cSt @40°C

Particle characteristics Not applicable to liquids

9.2 Other information

> VOC Content g/l: 320

Grams of VOC per liter of coating product as applied per ISO 11890-1 and/or ISO 11890-2.

Specific Gravity (g/cm3) 1.36

SECTION 10: Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No reactivity hazards known under normal storage and use conditions.

10.4 Conditions to avoid

Avoid heat, sparks, flames and other ignition sources.

10.5 Incompatible materials

Keep away from strong oxidising agents and strongly acid or alkaline materials.

10.6 Hazardous decomposition products

In case of fire or hot work operations, hazardous decomposition products may be formed such as: Carbon monoxide (CO),

carbon dioxide (CO2), oxides of nitrogen (NOx).

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute Toxicity:

Oral LD50: No Information Inhalation LC50: No Information

Dermal LD50: No information available on the product itself as the product is not tested.

Irritation: Irritating to skin.

Corrosivity: Causes serious eye damage.

Sensitization: May cause an allergic skin reaction.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: Central nervous system depression.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name According to EEC	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
13463-67-7	titanium dioxide	>5000 mg/kg (oral-rat)	10000 mg/kg	No information	No information	>6.82 mg/L (inh-rat-4h)
1330-20-7	xylene	>2000 mg/kg (oral-rat)	1100 mg/kg (ATE dermal- rabbit)	11 mg/L (ATE inh/vapour)	4500 ppmV (ATE inh - Gas)	1.5 mg/L (ATE inh/dust/mist)
123-86-4	n-butyl acetate	10760 mg/kg (rat-oral)	14112 mg/Kg (rabbit-dermal)	23.4 mg/l/4/h (rat)	No information	No information
71-36-3	Butan-1-ol	790 mg/kg (oral-rat)	3430 mg/kg (dermal-rabbit)	8000 mg/l 4hrs rat, inhalation	No information	No information
100-41-4	ethylbenzene	3500 mg/kg rat, oral	5001 mg/kg, rabbit	17.2 mg/L. rat, 4h	10000 ppm	1.5 mg/L
-	hydrocarbons, c9, aromatics	3492 mg/kg (oral-rat)	>3160 mg/kg (dermal-rabbit)	>6193 mg/L (inh-rat- vapour,4h)	No information	No information
67762-90-7	Siloxanes and Silicones, di- Me, reaction products with silica	6350 mg/kg (oral-rat)	>2000 mg/kg (dermal-rat)	No information	No information	No information
78-83-1	2-methylpropan-1-ol	24600 mg/kg (oral-rat)	> 2000 mg/kg (dermal - rabbit)	> 20 mg/L (Inhalation, rat, 6h)	8000 ppm	No information
1065336-91-	Reaction mass of bis (1,2,2,6,6-pentamethyl-4-pentamethyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	>2000 mg/kg (oral-rat)	>3000 mg/kg (dermal-rat)	No information	No Information	No Information

Additional Information:

This product may contain Ethyl Benzene, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. Corrosive - causes irreversible eye damage. Chronic exposure causes drying effect on the skin and eczema. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Gas or vapour is harmful on prolonged exposure or in high concentrations. Irritant of eyes and mucous membranes. CNS depressant. Inhalation is the main hazard in industrial use. The solvent vapours can be harmful and cause headaches, nausea, and intoxication. Acts as a defatting agent on skin. This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. Chronic exposure has been associated with various neurotoxic effects including permanent brain damage. Inhalation of vapour or mist can cause headache, nausea, irritation of nose, throat, and lungs.

11.2 Information on other hazards

Endocrine disrupting properties - Toxicity

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

SECTION 12: Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information
No information
No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.

assessment:

12.6 Endocrine disrupting properties

Endocrine disrupting properties - Ecotoxicity

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

12.7 Other adverse effects: No information

CAS-No.	Name According to EEC	EC50 48hr	IC50 72hr	LC50 96hr
13463-67-7	titanium dioxide	>100 mg/l (EC50, 48h, Daphnia magna OECD202)	16 mg/l (EC50, 72h, Pseudokirchnerella subcapitata)	>100 mg/l (EC50, 96h, Oncorhynchus Mykiss OECD203)
1330-20-7	xylene	1 - 5 mg/L (Daphnia magna)	3 - 5 mg/L (Selenastrum sp.)	2 - 11 mg/L (Roccus saxatilis), 8.2 mg/L (Salmo gairdneri), 13.5 mg/L (Lepomis macrichirus), 21.0 mg/L (Pimephales promelas)
123-86-4	n-butyl acetate	44 mg/L (Daphnia magna)	648 mg/L (Desmodesmus subspicatus)	18 mg/L (Pimephales promelas)

71-36-3	Butan-1-ol	No information	No information	1740 mg/l (Pimephales promelas)
100-41-4	ethylbenzene	1.8 - 2.4 mg/L (Daphnia magna)	5.4 mg/L (Pseudokirchneriella subcapitata)	4.2 mg/L (Oncorhynchus mykissl)
-	hydrocarbons, c9, aromatics	3.2 mg/L (Daphnia magna)	No information	9.2 mg/L (Oncorhynchus mykiss)
78-83-1	2-methylpropan-1-ol	1100 mg/L (Daphnia magna)	1799 mg/L (Scenedesmus subspicatus)	1430 mg/L (Pimephales promelas)
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethyl-4- 5 piperidyl) sebacate and methyl 1,2,2,6,6- pentamethyl-4-piperidyl sebacate	No information	1.68 mg/L (desmodesmus subspicatus)	0.9 mg/L (brachydanio rerio)

SECTION 13: Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Empty containers should be taken to an approved waste handling site for recycling or disposal. Rags/wiping cloths and the like, moistened with flammable liquids, must be discarded into designated fireproof buckets. Dispose of waste material at an approved (hazardous) waste treatment/disposal facility in accordance with applicable local state, and federal regulations. Do not dispose of waste with normal garbage, or to sewer systems.

European Waste Code: 08 01 11* **Packaging Waste Code:** 15 01 10*

SECTION 14: Transport Information

		ADR/RID	ADN	IMDG	IATA
14.1	UN-number or ID number	UN1263	UN1263	UN1263	UN1263
14.2	UN proper shipping name	PAINT	PAINT	PAINT	PAINT
14.3	Transport Hazard Class(es)	3	3	3	3
14.4	Packing Group	III	Ш	III	III
14.5	Enviromental Hazards	Marine pollutant: No	Marine pollutant: No	Marine pollutant: No	Marine pollutant: No

14.6 Special precautions for user Not applicableEmS-No.: F-E, S-E

14.7 Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Denmark Product Registration Number: Not available

Danish MAL Code: Not available

Danish MAL Code - Mixture: Not available

Sweden Product Registration Number: Not available

Norway Product Registration Number: P-304242

WGK Class: 2

Covered by Directive 2012/18/EC (Seveso III): P5c

Restrictions to product or to substances according to Annex XVII, Regulation (CE) 1907/2006:

Annex XIV - Annex XIV, Regulation (CE) 1907/2006 - Authorisation List:

CAS-No. Name According to EEC

Not Applicable

SVHC - Substances of very high concern (Candidate List - Art. 59 REACH):

CAS-No. Name According to EEC

Not Applicable

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other Information

Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Reasons for revision

Changes have been made to Section 2 of the Safety Data Sheet (SDS). Please refer to the Hazard Identification information in Section 2 of this SDS. Changes have been made to Section 9 of the Safety Data Sheet (SDS). Please refer to the Physical and Chemical Properties information in Section 9 of this SDS. . This safety data sheet (SDS) applies to several colours and is based on the colour with the most stringent classification. Thus, for some colours, there may be a different classification than the one given in section 2.2 in this SDS.

List of References

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark
- Joint Research Centre in Ispra, Italy
- Regulation (EC) 1272/2008 with subsequent amendments
- Regulation (EC) 1907/2006 with subsequent amendments
- Commission Regulation (EU) 2020/878
- Eu Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union

US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million

mg/m3 Milligrams per cubic meter TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration
IC50 Half maximal inhibitory concentration
PBT Persistent bioaccumulative toxic chemical
vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as modified

by the Protocol of 1978

IBC International Bulk Container
RTI Respiratory Tract Irritation

NE Narcotic Effects

IMO International Maritime Organization

Note P: The classification as a carcinogen or mutagen need not apply; the substance contains

less than 0,1 % w/w benzene

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder

form containing 1 % or more of titanium dioxide which is in the form of or

incorporated in particles with aerodynamic diameter \leq 10 μ m.

For further information, please contact: Regulatory Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.