

Cl/SfB		Yt3	
CAW Z20			
Uniclass L6732:P74			

## Description

CT600 is a high strength contact adhesive made from a blend of synthetic rubber and resin that is supplied in an easy-to-use 500 ml handheld sprayable canister.

## Colour

Light yellow

## Packaging

500 ml can (12 per carton)

## Technical Information

Characteristic	Results (Typical Values)
Composition	A blend of synthetic rubber and resin
System	Solvent evaporation
Specific Gravity	1.22
Viscosity (at 20°C)	Sprayable
Flash Point	-40°C
Coverage	5 m <sup>2</sup> of bonded area per 500 ml canister
Drying Time (at 20°C)	2- 3 minutes
Application Temperature	+5°C to +30°C
Service Temperature	-20°C to +65°C
Storage	Store in shaded, dry conditions between 0°C and +30°C
Shelf Life	12 months when stored as recommended in original, unopened containers

## Necessary Tools

- Hand held canister- no tools required.

## Protective Equipment

USE IN WELL VENTILATED CONDITIONS and ensure all recommended protective equipment is worn during handling & use of this product. For full recommendation, refer to safety data sheet.

## Preparation

- Surfaces must be clean, dry, smooth, firm and free from any traces of contaminant which may affect adhesion.
- Metal surfaces must be degreased using AT200 High Strength Cleaner and completely dry before bonding.

## Application

- Shake the can thoroughly before use.
- Remove the cap and turn the nozzle to the desired spray width.
- Hold the can 20 cm to 25 cm away from the surface and spray onto the substrate to be bonded.
- After use turn the can upside down and press the spray nozzle until it is clear of adhesive. This will prevent a blockage in the nozzle.

## ONE-WAY WET STICK:

- Apply to porous materials such as cardboard, fabric, paper, etc., apply to one surface and press both surfaces together immediately.



## CT600

## Sprayable Contact Adhesive



## Usage / Purpose

CT600 is a high strength contact adhesive in an easy-to-use 500 ml handheld canister. It is ideal for quick and simple bonding of many common materials, including: wood, cardboard, fibrous insulation materials, paper, plastics, canvas, cork, rubber, fabrics and foam, either to themselves or onto brickwork, concrete, stone and plaster.

## Key Benefits

- A powerful contact adhesive in a convenient easy-to-use 500 ml canister
- Dries rapidly to form a high strength bond with porous and non-porous materials
- Integral adjustable nozzle allows precise control of the spray pattern to suit any particular job
- Versatile formulation - can be used as a one-way, contact or temporary tacking adhesive
- Excellent coverage - up to 5 m<sup>2</sup> of bonded area from a single canister

**TWO-WAY WET STICK:**

- For bonding non-porous substrates, apply to both surfaces, allow to dry for 2 to 3 minutes and then press both surfaces together.

**TEMPORARY BOND:**

- Spray on to one surface, allow the coating to dry for 3 to 5 minutes and press into position.

**Cleaning**

Clean any surplus adhesive using AT200 High Strength Cleaner.

**Please Note**

Not suitable for bonding expanded polystyrene.

**Health & Safety Precautions**

Safety data sheet must be read and understood before use. Extremely flammable - keep away from open flames and other ignition sources.

**Technical Service**

Tremco CPG UK Limited has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

**Guarantee / Warranty**

Tremco CPG UK Limited products are manufactured to rigid standards of quality. Any product which has been applied (a) in

accordance with Tremco CPG UK Limited written instructions and (b) in any application recommended by Tremco CPG UK Limited, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct. Tremco CPG UK Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.

**Tremco CPG UK Limited**

Coupland Road  
Hindley Green, Wigan WN2 4HT  
United Kingdom  
T: +44 1942 251400  
F: +44 1942 251410

info.uk@tremcocpg.com  
www.tremcocpg.eu