

## Product data sheet

### Premier

#### AR915



ARRONE mortice apartment lock case:

- Function: Latch bolt and deadbolt with escape operation
- Forend/strike material: Stainless steel
- Forend type: Single
- Strike type: Adjustable
- Follower: 8 mm split follower with self locating plate to allow easy reversibility of the escape function. Supplied with AR228A (100 mm) and AR228B (120 mm) spindles for split follower lock
- CE Marked: AG0067, ABB010, UKCA Marked: AG7668
  - **BS EN 12209:** 3 | X | 8 | 1\* | 0 | G | 4 | B | A | 3 | 0
  - **BS EN 179:** 3 | 7 | 6 | B | 1 | 4 | 4 | 1 | A | B
  - **BS EN 179:** 3 | 7 | 6 | B | 1 | 4 | 4 | 1 | A | D
- Certifire approved: CF530, CE DOP: HUK0012 and HUK0035, UKCA DOP: HUK0012-UK and HUK0035-UK
- Testing: **BS EN 1634-1.** Assessed for use on 30, 60, 90 and 120 minute timber fire doors and 240 minutes steel fire doors.
- **To comply with BS EN 179 certification, only lever handles and associated fixings included in the test evidence must be used.**
- Meets dimensional recommendations of **BS 8300** and ADM for locks
- \* The AR915 series lock case has been successfully fire tested with the use of an intumescent kit. The supply and fitting of this intumescent kit is essential to the products compliance with the fire test and CE marking evidence it has gained. HOPPE takes no responsibility for any locks purchased and fitted without sufficient intumescent protection.

Article number	50015679
Product ref.	AR915/ADJ-OEM-R-60-SSS
EAN-Code	5051358007796
Country of origin	Portugal
CN-Code	83014019
Door thickness	44/54 mm
Follower	8 mm
Backset	60 mm, pierced for furniture and es-cutcheons at 38 mm centres
(Key)Hole size	Euro profile cylinder
Key hole distance	72 mm
Door type	wooden door/metal door
Fixings	Timber door and metal door
Corner	Radius Corner - Adjustable Strike
Shape	radiused
Finish	Satin Stainless Steel
Face plate finish	F69 satin stainless steel
Range	ARRONE Range
Packing unit	0
Outer carton	0

