

## Product data sheet

Plus

AR-E150F/42K-A2



|                   |                                                                   |
|-------------------|-------------------------------------------------------------------|
| Article number    | 87109373                                                          |
| Product ref.      | AR963/60-SP-SSS                                                   |
| EAN-Code          | 5051358049659                                                     |
| Country of origin | China                                                             |
| CN-Code           | 83024110                                                          |
| Door thickness    | 40-50 mm                                                          |
| Spindle size      | 8 mm                                                              |
| Spindle length    |                                                                   |
| Door type         | wooden door                                                       |
| Fixings           | 8 wood screws, 2 bolts & allen key, A2 stainless steel, pozidrive |
| Bearing           | sprung                                                            |
| Connection        | breakthrough spindle                                              |
| Spindle size      | 8 mm                                                              |
| Finish            | Satin Stainless Steel                                             |
| Range             | ARRONE Range                                                      |
| Packing unit      | 1                                                                 |
| Outer carton      | 20                                                                |

ARRONE stainless steel lever handle set on rose for interior doors:

- Material: Stainless steel grade 304
- Bearing: Fixed/movable
- Connection: Solid spindle with eccentric hole on both ends
- Base: Stainless steel
- Fixing: Bolt through and wood screws
- Testing: Included in a successful fire test to **BS EN 1634** Part 1. Assessed for use on 30 and 60 minutes timber fire doors

