

Product data sheet

Premier

AR5200



ARRONE overhead door closing device:

- Power size: 3 to 5 adjustable by spring tension (Size 2 by template)
- Function: Closing, latching, backcheck
- Cover: Slide cover
- Maximum door width: 1,250 mm (Fig 1), 1,100 mm (Fig 6 and Fig 61)
- Maximum door weight: 100 kg (Fig 1), 80 kg (Fig 6 and Fig 61)
- Arm application: Fig 1, Fig 6 and Fig 61 fixing positions
- Successfully type tested for conformity to all the requirements of **BS EN 1154:1997**
 - Door mount pull (Fig 1): 4 | 8 | 5/2 | 1* | 1 | 4
 - Door mount push (Fig 6): 3 | 8 | 4/3 | 1* | 1 | 4
 - Transom mount push (Fig 61): 4 | 8 | 4/2 | 1* | 1 | 4
- Included in a successful fire test to **BS EN 1634** Part 1. Assessed for use on 30, 60 and 120 minutes timber fire doors and 240 minutes on steel fire doors.
- CE Marked: AD0239, UKCA Marked: AD7685
- Certifire approved: CF295, CE DOP: HUK0005, UKCA DOP: HUK0005-UK

Article number	87112570
Product ref.	AR5200-SE
EAN-Code	5051358071995
Country of origin	Taiwan
CN-Code	83026000
Door type	wooden door
Maximum door width	1250 mm
Maximum door weight	100 kg
Arm Application	figure 1, 6 and 61
Mechanism function	Backcheck, template + spring adjustment, closing/latching speed
Mechanism type	Rack & pinion
Fixings	Timber door
Shape	Trim Plate
Power size	2 to 5
Opening Angle	max. 180° opening
Mechanism dimensions and fixing centres	236x60x38.5 mm; centres 95x195x45 mm
Arm type	Scissor arm, fixed joint, flat form, adjustable
Finish	Silver Enamel
Finish of the cover	Silver Enamel
Arm finish	Silver Enamel
Range	ARRONE Range
Packing unit	1
Outer carton	6

