

Product Description

OBEX CORTEX 0771FR Class B Paste Adhesive is a high-quality, moisture-curing adhesive, used for bonding and sealing Interface Sealing Membranes. Developed for use in applications that require fire-classified products.

Product Specifications

Colour	Black
Pack	12 x 600ml foil
Shelf life	12 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

Product Applications

- » For bonding and sealing of membranes onto other building substrates. Porous surfaces should be primed with OBEX CORTEX 0787FR Class B Primer. Primer is not required for non-porous substrates.

Technical Data

Fire Classification	B-s1,d0
Chemical Base	Oxime
Consistency	Stable Paste
Curing System	Moisture Curing
Curing Time	2mm/24 hours (23°C, %50 R.H)
Shore A	20, DIN 53 505 (N/mm ²)
Density	1.40 ± 0.03gr/cm ³
Elongation	462%
Maximum Allowed Distortion	25%
Temperature Resistance	-50°C to 120°C
Tensile Strength	1.0 MPa
Application Temperature	5°C to 40°C

Application Method

- » Applied using a manual or pneumatic caulking gun. Surfaces to be clean, dry and free of dust, grease and oils etc.
- » Clean with OBEX CORTEX 0795 Cleaning Wash immediately after use.
- » Repair with the same material.


Associated Products

- » OBEX CORTEX 0500FR Class B Interface Sealing Membrane
- » OBEX CORTEX 0787FR Class B Primer

Additional Important Information

- » Do not use on natural stones like marble and granite (staining).
- » It is the responsibility of the user to test for compatibility.
- » Consult the OBEX Technical Team with any queries.

Installation Guide*



Scan the QR code for the Installation Guide, to ensure an accurate and compliant install.

Alternatively follow this link:
obexuk.qrd.by/0500fr-install

*Install Guide for 0500FR, which 0771FR is used with.