## MANOR PRODUCT DATA SHEET



## **THINNERS & CLEANERS**

Name	Description	Manor Code
2 PACK EPOXY THINNER	A medium/fast thinner suitable for use with most two pack epoxy products. Fast evaporating for use with primers but with adequate "wet edge" to give good flow and gloss for finishing coats	2PAKTHN
2 PACK POLYURETHANE THINNER	The standard thinner for use with Manor 2 Pack Acrylic Polyurethane	2THINNS
2 PACK POLYURETHANE SLOW THINNER	A slower evaporating thinner for use where longer wet edge times are required, for example to prevent dry spray when painting large components, and whenever the temperature of the spray shop rises above 25°C	2THINSL
FAST FLASH THINNER	Used as a rapid evaporating or universal thinner, particularly in High Build Vinyl, and QD One Coat Gloss	FFTHINN
SPRAY EQUIPMENT CLEANER	A budget priced reclaimed cellulose solvent suitable for removing most solvent based paints and lacquers from spray equipment and brushes.	GUNCTHN
INDUSTRIAL THINNER	The most commonly used medium/fast thinner in the industrial finishing market.	INDUTHN
LOW ODUR WHITE SPIRIT	Often referred to as Turpentine Substitute (Turps). Used mainly in the decorative paint sector where it is suitable for thinning Manor Gloss, Manor Undercoat, Manor Wood Primers etc.	WSPIRIT
PANEL CLEANER	A rapid evaporating surface cleaning solvent ideal for processes requiring a fast flash off for painting to follow immediately after surface cleaning. Recommended for any small surface area cleaning.	PANELCL
RETARDER THINNER GF	A <i>very useful, slow</i> evaporating high flash point solvent for use with many industrial coatings to extend the "wet edge and flash off" time. <i>In Air Drying Finishes</i> The addition of this solvent is useful in controlling micro blistering and dry spray. Does not affect the overall drying of the product, only the "flash off" times. <i>In Stoving Finishes</i>	GFSTHNN
	Will help eliminate "solvent boil" during the stoving process,	

Manor Coating Systems Limited, Otley Road, Shipley BD17 7DP Tel: 01274 587351 <a href="https://www.manorcoatingsystems.co.uk">www.manorcoatingsystems.co.uk</a>

Code Thinners & Cleaners Version Number 9 Issued July 2022 Reference Word

schedules are unaffected.

improve flow, and minimise dry spray effects. Stoving

## When Dipping

May also be used with most air drying and stoving finishes to minimise runs and sags, and improve uniformity of the film

STOVING THINNER This standard medium to fast evaporating thinner is suitable STOVTHN

for general purpose use with Manor Stoving Finishes

SYNCVTH

SYNTHETIC THINNER

CV

A medium evaporating thinner designed for use in Manor UPF Primer, 1 Pack Polyurethane, 1 Pack Polyurethane QD,

and Chassis Paint.

**Shelf life** Store in cool, dry conditions, typically 5-25 C. After a period of storage the

product should be thoroughly sirred. Usable life is 2 years from the date of

manufacture in unopened containers.

Safety Precautions Refer to the Manor Safety Data Sheet

**Limitations**The information given in this data sheet is based on experience and is accurate to the best of our knowledge. No guarantee should be implied

however, since the conditions of use are beyond our control. This data sheet

does not constitute a specification.

A Painting Guide can be accessed via our website which provides additional

information on paint and painting and definitions of terminology.

In case of doubt as to the suitability of the product please consult our Technical Department. If you are advised that the paint can be used in a manner not specified on this datasheet our Technical Department will confirm this to you in writing. Do not use paint prior to receiving this

confirmation.

References to other primers, topcoats, cleaners and thinners are to the

Manor Product of that name only.

This data sheet supersedes all previous issues.