

SOTERIAN

UAP



Application

Fire resisting, Secured by Design and/or PAS24 timber doorsets

Fixing

Bolted together

Performance

TS008 certified
Certifire approved
Smoke tested in accordance with BS EN 1634-3
Salt spray tested to BS EN 1670 - Class 5
20,000 cycles

Material

Aluminium (stainless steel Nanocoat option available)

Door thickness (mm)

44 54 & 58

Size (mm)

305x75 (260x53 internal dimension)

Colours

Internal - White (**WHT**) / Gold Anodised (**GAA**) /
Polished Silver (**PSL**) / Satin Silver Anodised (**SSA**)

External Frame - Black (**BLK**) / Gold Anodised (**GAA**) /
Polished Silver (**PSA**) / Satin Silver Anodised (**SSA**) /
Powder Coated White (**WHT**)

Door types

Composite (**CIN**) and Timber (**TIN**)

Fire rating

FD30 (**30**) and FD60 (**60**).
(FD60 only available for timber doors)

Order codes

Internal

TS008/- + Fire Rating + Door thickness + Door Type + /Finish

eg. **TS008/3044CIN/WHT**
(44mm, FD30, Composite door, White finish)

External Frame

TS008/EXFR/ + /Finish

eg. **TS008/EXFR/BLK** (External FR Frame, Black finish)

Dimensions



 5 Regents Drive
Prudhoe
Northumberland
NE42 6PX



norseal.co.uk



sales@norseal.co.uk



01661 830088

Registered in Companies House Cardiff No. 04317595 VAT Reg. No. 733 9466 08