

SCC-2

35" Standard Controller Cabinet

The SCC-2 Standard Controller Cabinet is the larger version of our modular electrical and wire management enclosure system for the TrolMaster HCS-2 and NFS-2 Control system.

The cabinet is designed to allow TrolMaster's HCS-2 and NFS-2 controllers to be installed in a clean and professional manner. A pre-cut opening allows the TrolMaster's main controller Hydro-X Pro (HCS-2) or Aqua-X Pro (NFS-2) to be fitted and provide a preprofessional and clean installation for your control system. All device stations can be mounted inside the IP56 rated electrical cabinet to keep the device stations clean and dry. Users can safely mount and neatly organize the power supplies, modules, and RJ12 cables with ease.



***Note:** In order to achieve the IP56 standard, you must use the provided "controller rubber gasket" and perfectly fit the gasket between the controller and cabinet door.

Specifications

SCC-2

Power Input

Voltage 120V

Max Amps 15A

Working Environments

Ingress Protection IP56

Temperature 32°F - 104°F / 0°C - 40°C

Cabinet Capacity

Splitter Board Group #1 10 ports (top)

Splitter Board Group #2 6 ports (top)

Splitter Board Group #3 17 ports (top)

Splitter Board Group #4 4 x 4 ports (Detachable Splitter Bars)
2 ports (Device)
6 ports (Bottom)

Power Outlet 8+1+6

Max No. of Modules (TS/HS/TSH/VPD) 16

Cabinet Dimension and Weight

Size 6.26" / 159.1mm (L) x 18" / 457.2mm (W) x 35" / 889mm (H)

Weight 41.09 lbs / 18.64 kg

Packaging Dimensions and G.W.

Size 10.43" / 265mm (L) x 21.65" / 550mm (W) x 38.39" / 975mm (H)

Weight 48.72 lbs / 22.1 kg

Package Content

Controller Cabinet 1 pc

Controller Rubber Gasket 1 pc

Long RJ-12 Cables 4 pcs

Short RJ-12 Cables 26 pcs

Power Cables (for OA6 modules) 8 pcs

OA6-24 Screw Set 18 pcs

Installation Manual 1 pc

