



White-Out


Privacy

SKU: RA1526

GSW® White Out gloss window film offers total privacy, inside and out. The window film allows virtually no light to pass through and is therefore an effective solution for privacy protection, ideal for hiding for example warehouse stock or a storage space.


Features:

- Perfect for making situations light and airy.**
- Ideal for hiding your view.**
- Creates an attractive appearance on the facade.**
- Glass gets a longer lifespan.**
- Let no light through.**
- White gloss look.**



PRODUCT PERFORMANCE

UV protection	99%
Light transmission	1%
Reflection of visible light outside	88%
Reflection of visible light inside	88%
Reflection of solar energy	67%
Absorption of solar energy	27%
Transmission of solar energy	6%
Reduction of reflection	95%
Sun transmission	14%
Rejected solar energy single glazing	80%
Rejected solar energy double glazing	86%
G-value	0.13
U-value single	5
U-value double	
Shade coefficient	0.1



PRIVACY

PROFESSIONAL WINDOWFILM
VISIT GSWFILM.COM

Contact sales +31 (0)299-323122 info@gswfilm.com

White-Out

Privacy

SKU: RA1526

GLASS TYPES	SUITABLE
Clear single pane	Yes
Tinted single pane	Yes
Reflective tinted single pane	Yes
Clear double pane	Yes
Tinted double pane	no
Reflective tinted double pane	no
Gas-filled double pane - Low E	no
Stadip ext. clear double pane	no
Stadip int. clear double pane	no
Triple glazed	no
Acrylic 4 mm	Yes
Polycarbonate 4 mm	no

PRODUCT FEATURES	
Width(s)	152 cm
Length(s)	30 meters
Film thickness	75 μ
Material	PET
Storage period	3 years
Storage temperature	-5 °C to '+40 °C
Fire class	EN13501-1
Manufacturer	

***Recommendations based on a glass surface of max. 2.5 m2. Contact us for further information.**

U-value


The lower the U-value, the better the thermal resistance of the foil, with less heat being lost to the outside.

Installation

Install the film with water and green Fairy dishwashing liquid. Under no circumstances use chemicals!

Maintenance

Do not clean the window film or attach stickers or other adhesives for at least 1 month after installation. The film can then be cleaned with water and green Fairy dishwashing liquid. Be careful not to use chemicals!



1. Hard scratch-resistant mat layer for long life and ease of maintenance when cleaning the windows.
2. Optically high-quality polyester, with metal particles against infrared radiation.
3. Optically high-quality polyester.
4. Self-adhesive glue, glass polymerization within 15 days.
5. Protective film, disposable after installation

PROFESSIONAL WINDOWFILM
VISIT [GSWFILM.COM](https://www.gswfilm.com)

GSW accepts no liability for administrative errors and reserves the right to change information without prior notice. This document does not create, specify, modify or replace any new or existing contractual obligations agreed between GSW and the user. Data calculated on the basis of film on clear glass of 3 mm thickness (*on double glass 4-16-4). GSW® is a registered trademark of Glass Solution Windowfilm B.V. ©2024 GSW



FREE SAMPLE