


# TECHNICAL DATA SHEET

## for appliance Well Done

according to Table 22 of the standard EN 16510-1:2022

Nº	Parameter	Unit	Explanation	Data for fuel wood
1*	$P_{nom}$	kW	The nominal heat output or a range of outputs (dependent on fuel types)	6,54
2*	$P_{SHnom}$	kW	The nominal space heat output or a range of outputs (dependent on fuel types)	
3*	$P_{Wnom}$	kW	The nominal water output (if an integral boiler is fitted) or a range of outputs (dependent on fuel types)	
4*	$P_{part}$	kW	The part load heat output or a range of outputs (dependent on fuel types)	
5*	$P_{SHpart}$	kW	The part load space heat output or a range of outputs (dependent on fuel types)	
6*	$P_{Wpart}$	kW	The part load water output (if an integral boiler is fitted) or a range of outputs (dependent on fuel types)	
7*	$P_{slow}$	kW	The heat output at slow combustion or a range of outputs (dependent on fuel types)	
8*	$P_{SHslow}$	kW	The space heat output at slow combustion or a range of outputs (dependent on fuel types)	
9*	$P_{Wslow}$	kW	The water heat output at slow combustion (if an integral boiler is fitted) or a range of outputs (dependent on fuel types)	
10*	$\eta_{nom}$	%	The appliance efficiency at nominal heat output	80,5
11*	$\eta_{part}$	%	The appliance efficiency at part load heat output	
12	$\eta_s$	%	The appliance seasonal space heating efficiency at nominal heat output	70,5
13	EEI	-	The energy efficiency index	104
14*	$CO_{nom}$ (13%O <sub>2</sub> )	mg/m <sup>3</sup>	CO emission at 13 % oxygen content at nominal heat output	872
15*	$CO_{part}$ (13%O <sub>2</sub> )	mg/m <sup>3</sup>	CO emission at 13 % oxygen content at part load heat output if specified	
16*	$CO_{slow}$ (13%O <sub>2</sub> )	mg/m <sup>3</sup>	CO emission at 13 % oxygen content at heat output at slow combustion if specified	
17*	$NOx_{nom}$ (13%O <sub>2</sub> )	mg/m <sup>3</sup>	NOx emission at 13 % oxygen content at nominal heat output	105
18*	$NOx_{part}$ (13%O <sub>2</sub> )	mg/m <sup>3</sup>	NOx emission at 13 % oxygen content at part load heat output if specified	
19*	$NOx_{slow}$ (13%O <sub>2</sub> )	mg/m <sup>3</sup>	NOx emission at 13 % oxygen content at heat output at slow combustion if specified	
20*	$OGC_{nom}$ (13%O <sub>2</sub> )	mg/m <sup>3</sup>	OGC emission at 13 % oxygen content at nominal heat output	69
21*	$OGC_{part}$ (13%O <sub>2</sub> )	mg/m <sup>3</sup>	OGC emission at 13 % oxygen content at part load heat output if specified	
22*	$OGC_{slow}$ (13%O <sub>2</sub> )	mg/m <sup>3</sup>	OGC emission at 13 % oxygen content at heat output at slow combustion if specified	
23*	$PM_{nom}$ (13%O <sub>2</sub> )	mg/m <sup>3</sup>	Particulate matter emission at 13 % oxygen content at nominal heat output	23,7
24*	$PM_{part}$ (13%O <sub>2</sub> )	mg/m <sup>3</sup>	Particulate matter emission at 13 % oxygen content at part load heat output if specified	
25*	$PM_{slow}$ (13%O <sub>2</sub> )	mg/m <sup>3</sup>	Particulate matter emission at 13 % oxygen content at heat output at slow combustion if specified	
26*	$p_{nom}$	Pa	Minimum flue draught at nominal heat output	12 +- 2

№	Parameter	Unit	Explanation	Data for fuel wood
27*	$p_{part}$	Pa	Minimum flue draught at part load heat output if specified	
28*	$p_{slow}$	Pa	Minimum flue draught at heat output at slow combustion if specified	
29*	$p_w$	bar	The permissible maximum water operating pressure	
30*	$d_R$	mm	The minimum distances from the rear to combustion material	
31*	$d_S$	mm	The minimum distances from the sides to combustion material	600
32*	$d_C$	mm	The minimum distances from the top to combustion material in the ceiling	700
33*	$d_P$	mm	The minimum distances from the front to combustion material	1200
34*	$d_F$	mm	The minimum distances from the front to combustion material in bottom front radiation area	700
35*	$d_L$	mm	The minimum distances from the front to combustion material in side front radiation area	900
36*	$d_B$	mm	The minimum distances below the bottom (not regarding feet) to combustible material	0
37	$d_{non}$	mm	The minimum distance to non-combustible walls	
38	s	mm	Protective insulation according to manufacturers instructions	
39	$e_{lsB}$	kW	The consumption of electrical auxiliary energy at standbay	
40	$e_{lmax}$	kW	The consumption of electrical auxiliary energy at nominal heat output	
41	$e_{lmin}$	kW	The consumption of electrical auxiliary energy at part load heat output	
42	E, f	V, Hz	Power supply voltage, frequency	
43	$W_{max}$	W	Maximum electric power input	
44	$T_{snom}$	°C	The flue gas outlet temperature at nominal heat output	177
45	$T_{spart}$	°C	The flue gas outlet temperature at part load heat output	
46	$T_{class}$	-	Chimney designation according to the appropriate chimney standard	
47	$\Phi_{f,g nom}$	g/s	The flue gas mass flow at nominal heat output	7,1
48	$\Phi_{f,g part}$	g/s	The flue gas mass flow at part heat output	
49	$V_h$	m <sup>3</sup> N/h	The standing air loss	
50	CON or INT	-	Indication whether the appliance is capable of continuous operation (CON); Indication whether the appliance is capable of intermittent operation (INT)	
51	$d_{out}$	mm	The diameter of the flue gas outlet	150
52	L, H, W	cm	The overall dimensions of the appliance (length, height, width)	51,2; 104; 44,4
53	m	kg	Mass of the appliance	120
54	$m_{chim}$	kg	The maximum load of a chimney the appliance may carry, to be rounded to the nearest integer	
55		-	“Read and follow the user operating instructions”	

\* - the parameters are also indicated on the CE marking label