



AMBER C

Inactinic film. Carefully applied to your windows, Amber C films are specially designed to filter out harmful UV rays, as well as 95% of visible light up to 420nm. This film will protect items and furnishings exposed to sunlight from fading and premature ageing.



Fire-resistance rating



Storage from -5°C to +40°C **3 YEARS**



REACH RoHS compliant RESPECTED

TECHNICAL DATA

Data calculated based on film applied to clear glass 3 mm thick (* on double glazing 4-16-4)

Ultraviolet transmission	0.5%
Visible light transmission	57%
Reflection of external visible light	7%
Reflection of internal visible light	7%
Total solar energy rejected	26%
Total solar energy rejected 2 *	25%
Solar ratio:	
Solar energy reflection	9%
Solar energy absorption	23%
Solar energy transmission	68%
Reduction in Solar Glare	18%
G-value	NC
U-value	NC
Shading coefficient	NC
Installation type	Interior
Roll length	30,5 m
Film composition	PET
Thickness	30 µ
Colour from the outside	Orange

MAINTENANCE

Use soapy water solution for cleaning. Do not clean for at least a month after installation and do not apply any type of stickers or adhesive on the film. For more information read our maintenance instructions and quality standards on www.solfilmsgrossisten.se

INSTALLATION ADVICE

Vertical installation and on standard glass surface *

Clear single pane	\
Tinted single pane	~
Reflective tinted single pane	~
Clear double pane	~
Tinted double pane	~
Reflective tinted double pane	~
Gas-filled double pane - Low E	~
STADIP EXT. clear double pane	~
STADIP INT. clear double pane	~

Recommended

* Recommendations provided on the basis of a glazed surface covering up to 2.5 m², contact us for definitive details or to obtain a thermal chock analysis report.

CONSTRUCTION

- 1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
- 2. Dyed polyester without optical distortion
- 3. PS adhesive, glass polymerization within
- 4. Protection release liner, disposable after installation

