



# CLEARBOARD

*This dry erase board transforms your glass surfaces in a real board for dry erase markers, while preserving total clarity and transparency.*



Fire-resistance rating  
**M1**



Storage from -5°C to +40°C  
**3 YEARS**



REACH RoHS compliant  
**RESPECTED**

## TECHNICAL DATA

Data calculated based on film applied to clear glass 3 mm thick (\* on double glazing 4-16-4)

Ultraviolet transmission	5%
Visible light transmission	85%
Reflection of external visible light	11%
Reflection of internal visible light	11%
Total solar energy rejected	19%
Total solar energy rejected 2 *	19%
Solar ratio:	
Solar energy reflection	9%
Solar energy absorption	14%
Solar energy transmission	77%
Reduction in Solar Glare	14%
G-value	0.83
U-value	5.7
Shading coefficient	0.9
Installation type	Interior
Roll length	30,5 m
Film composition	PET
Thickness	80 µ
Colour from the outside	Transparent

## MAINTENANCE

Use soapy water solution for cleaning. Do not clean for at least a month after installation and do not apply any type of stickers or adhesive on the film. For more information read our maintenance instructions and quality standards on [www.solfilmsgrossisten.se](http://www.solfilmsgrossisten.se)

## INSTALLATION ADVICE

Vertical installation and on standard glass surface \*

Clear single pane	✓
Tinted single pane	✓
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	✓
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✓
STADIP EXT. clear double pane	✓
STADIP INT. clear double pane	✓

✓ Yes   ! Caution   ✗ Not

*Recommended*

\* Recommendations provided on the basis of a glazed surface covering up to 2.5 m<sup>2</sup>.

## CONSTRUCTION

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. High optical quality polyester
3. Reinforced PS adhesive to accompany the elasticity of the film in case of impact, glass polymerization within 30 days
4. Protection release liner, disposable after installation

