



#### **DATA JAMMER**

Thanks to this polarizing film, create a blackout effect on your LCD or Plasma screens while preserving a perfect view through the glass.



# ٨

Fire-resistance rating



Storage from -5°C to +40°C **3 YEARS** 



REACH RoHS compliant **RESPECTED** 

## **TECHNICAL DATA**

Data calculated based on film applied to clear glass 3 mm thick (\* on double glazing 4-16-4)

Ultraviolet transmission	1%
Visible light transmission	44%
Reflection of external visible ligh	ht 8%
Reflection of internal visible ligh	nt 9%
Total solar energy rejected	30%
Total solar energy rejected 2 *	30%
Solar ratio:	
Solar energy reflection	NC
Solar energy absorption	NC
Solar energy transmission	NC
Reduction in Solar Glare	58%
G-value	NC
U-value	NC
Shading coefficient	NC
Installation type	Interior
Roll length	30,5 m
Film composition	PET + PVA
Thickness	132 μ
Colour from the outside	Transparent

# **MAINTENANCE**

Use soapy water solution for cleaning. Do not clean for at least a month after installation and do not apply any type of stickers or adhesive on the film. For more information read our maintenance instructions and quality standards on www.solfilmsgrossisten.se

### **INSTALLATION ADVICE**

Vertical installation and on standard glass surface \*

Clear single pane	<b>~</b>
Tinted single pane	<b>✓</b>
Reflective tinted single pane	<b>~</b>
Clear double pane	<b>~</b>
Tinted double pane	<b>V</b>
Reflective tinted double pane	<b>~</b>
Gas-filled double pane - Low E	<b>V</b>
STADIP EXT. clear double pane	<b>~</b>
STADIP INT. clear double pane	1

✓ Yes ! Caution 

X Not

Recommended

\* Recommendations provided on the basis of a glazed surface covering up to  $2.5 \, \text{m}^2$ .

### CONSTRUCTION

- Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
- 2. PVA film
- **3.** PS adhesive, polymerizes with glass within 15 days
- 4. Polarizing film

