



MULTI PROTEC 4 C

This multi-layer film has many lives! Indeed, thanks to its 4 layers of 100 microns, it will protect your surfaces from graffiti and tags. Once the film is too visually damaged, you can simply remove the layer. You have 4 layers before you have to install a new film. In addition, this film will also reinforce your windows against accidents, aggression and explosion risks.



Fire-resistance rating



Storage from -5°C to +40°C
3 YEARS



REACH RoHS compliant
RESPECTED

TECHNICAL DATA

Data calculated based on film applied to clear glass 3 mm thick (* on double glazing 4-16-4)

Ultraviolet transmission	2%
Visible light transmission	82%
Reflection of external visible light	11%
Reflection of internal visible light	11%
Total solar energy rejected	19%
Total solar energy rejected 2 *	19%
Solar ratio:	
Solar energy reflection	9%
Solar energy absorption	14%
Solar energy transmission	77%
Reduction in Solar Glare	17%
G-value	0.83
U-value	5.7
Shading coefficient	0.9
Installation type	Interior
Roll length	30,5 m
Film composition	PET
Thickness	485 µ
Colour from the outside	Transparent

MAINTENANCE

Use soapy water solution for cleaning. Do not clean for at least a month after installation and do not apply any type of stickers or adhesive on the film. For more information read our maintenance instructions and quality standards on www.solfilmsgrossisten.se

INSTALLATION ADVICE

Vertical installation and on standard glass surface *

Clear single pane	✓
Tinted single pane	✓
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	✓
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✓
STADIP EXT. clear double pane	✓
STADIP INT. clear double pane	✓

✓ Yes ! Caution ✗ Not

Recommended

** Recommendations provided on the basis of a glazed surface covering up to 2.5 m².*

CONSTRUCTION

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. 100µ high optical quality polyester
3. Non permanent PS adhesive
4. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
5. 100µ high optical quality polyester
6. Non permanent PS adhesive
7. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
8. 100µ high optical quality polyester
9. Non permanent PS adhesive
10. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
11. 100µ high optical quality polyester
12. Non permanent PS adhesive
13. Protection release liner, disposable after installation