



#### **RASPBERRY**

Applied to clear glass, the transparent Raspberry film bestows a red/pink tint to the glass without diminishing its transparent properties. It is the perfect way to enliven any interior glazing (such as partitions, shower screens, etc.) with a touch of colour.



# ٨

Fire-resistance rating **M1** 



Storage from -5°C to +40°C **3 YEARS** 



REACH ROHS compliant **RESPECTED** 

### **TECHNICAL DATA**

Data calculated based on film applied to clear glass 3 mm thick (\* on double glazing 4-16-4)

Ultraviolet transmission	1%
Visible light transmission	22%
Reflection of external visible light	10%
Reflection of internal visible light	10%
Total solar energy rejected	36%
Total solar energy rejected 2 *	32%
Solar ratio:	
Solar energy reflection	11%
Solar energy absorption	47%
Solar energy transmission	42%
Reduction in Solar Glare	80%
G-value	0.69
U-value	5.7
Shading coefficient	NC
Installation type	Interior
Roll length	30,5 m
Film composition	PET
Thickness	40 μ
Colour from the outside	Raspberry

## **MAINTENANCE**

Use soapy water solution for cleaning. Do not clean for at least a month after installation and do not apply any type of stickers or adhesive on the film. For more information read our maintenance instructions and quality standards on www.solfilmsgrossisten.se

#### **INSTALLATION ADVICE**

Vertical installation and on standard glass surface \*

Clear single pane	<b>~</b>
Tinted single pane	
Reflective tinted single pane	<b>~</b>
Clear double pane	1
Tinted double pane	. !
Reflective tinted double pane	<b>~</b>
Gas-filled double pane - Low E	1
STADIP EXT. clear double pane	1
STADIP INT. clear double pane	X

✓ Yes Caution X Not

Recommended

\* Recommendations provided on the basis of a glazed surface covering up to 2.5 m², contact us for definitive details or to obtain a thermal chock analysis report.

#### CONSTRUCTION

- Common scratch-resistant hard coat for durability and ease of maintenance when cleaning windows
- 2. High-quality polyester without optical distortion
- **3.** PS adhesive, cures with glass within 15 days
- **4.** Adhesive protection liner, disposable after installation

