




AMPAG BOXER Y TRANSIT

STRAPPING MACHINE

Cyklop®

Ampag Boxer Y Transit

STRAPPING MACHINE

Fully automatic strapping with PP strap

The Ampag Boxer Y TR strapping machine is a very fast strapping machine with a strapping head on the side of the machine. This makes the strapping machine resistant to dust, sand and dirt. The Ampag Boxer Y TR is suitable for strapping with 5, 9 or 12 mm PP strap. The machine is low-maintenance and extremely suitable for intensive use with high production numbers.
The strapping machine can make up to 35 straps per minute.

Advantages

- For PP strap 5 – 9 – 12 mm
- Automatic strap input and output
- Strapping head on the side - resistant to dust, sand and dirt
- Ready for operation within 30 seconds
- Up to 35 straps per minute
- End of strap signaling
- Sealing with welding tongue
- Extremely suitable for integration into existing lines
- Complete system with transport and control



< Click here for a video of the Ampag Boxer Y TR >



Technical data	
Speed	Up to 40 straps/minute
Consumable	PP strap: 5, 9, or 12 mm
Min. package dimensions (L x W x D)	170 x 30 x 180 mm
Max. package weight	Dependent on transport system
Strap coil	Core 200 mm Outer diameter 420 mm Width 190 mm
Strap tension	50 – 800 N
Strapping	Heat seal
Noise	78 - 85 dB(A)
Warm up time	30 seconds
Power supply	400 V, 3 phase, 50 Hz

Cyklop International
Industriestraße 133, D-50996 Köln
(Rodenkirchen)
Postfach / P.O. Box 50 12 20,
D-50972 Köln (Rodenkirchen)

+49 (0) 2236 6020
www.cyklop.com
info@cyklop.com

Cyklop®

©2021 Cyklop International - All rights reserved - Specifications are subject to change without notice