

# FROM THE FOUNDER OF THE #VIKISEWS BRAND

---



Back in 2016, when I was working on my first set of sewing instructions, I was trying to write them in such a way that even a complete beginner could easily understand and use them to create their very first garment. These instructions laid the foundation for the Vikisews brand, its vision and its mission. I wanted to create modern patterns with the most detailed and clear instructions.

Now, with each new collection we are constantly improving our instructions, amending them and adding more relevant details. By the time the final product reaches you, our drafters, correctors, and editors would have spent weeks perfecting every word and every photograph. If you compile a few of our instructions together, you will get a sewing manual that will assist you in sewing all kinds of garments at any difficulty level.

And I would be very happy if these instructions helped you to turn your hobby into a lifelong passion... Enjoy the process! Create your ultimate dream wardrobe! Wear your garments proudly for years to come!

If you have any questions, please contact us at [info@vikisews.com](mailto:info@vikisews.com) - we are always there to help.



## HILARY PATTERN DESCRIPTION

---

Hilary is a pair of close-fitting trousers with a straight silhouette. The front features angled decorative double-welt pockets on both sides. The back has waist darts and a horizontal functional welt pocket on the right. The top edge of the contour waistband sits on the natural waistline. The waistband has belt loops and fastens with a hook and eye. The trousers have a fly front zipper. The inseams have high slits at the bottom. The belt loops and slits feature decorative topstitching. Hilary is below-ankle length with allowance for the heel.



## IMPORTANT!

---

The contents of this pattern are copyright protected and belong exclusively to VikiSews. You may use VikiSews patterns for personal use. It is prohibited to share VikiSews patterns and instructions with third parties, as well as to publish patterns and instructions online for public access. According to part 1 of clause 1252 and clause 1301 of the Civil Code of the Russian Federation, failure to comply with the mentioned rules constitutes a breach of the legislation in force in the field of copyright and entails liability of the violator. Illegal use or distribution will be prosecuted in accordance with legislation.

You may use VikiSews patterns for commercial use, to sew custom-made garments and/or create fashion collections, on the condition that the patterns are solely used in a manufacturing setting and are not further shared with individuals.

## TOTAL EASE ALLOWANCE

---

Waistline ease, cm

Hipline ease, cm

2.7-2.8

1.4-3.8

## GARMENT LENGTH, CM

---

Height, cm

Side seam length including waistband, cm

1 (154-160)

106.6-108.6

2 (162-168)

110.9-112.9

3 (170-176)

115.2-117.1

4 (178-184)

119.5-121.4

## FINISHED TROUSER HEM WIDTH, CM

---

Size

34

36

38

40

42

44

46

48

50

52

17.2

17.8

18.2

18.8

19.2

19.8

20.2

20.8

21.2

21.8

3. Lightweight fusible knit or woven interfacing, 140cm wide, for all sizes in all heights, in meters:

Size	34	36	38	40	42	44	46	48	50	52
Yardage	0.25	0.3	0.3	0.3	0.3	0.3	0.35	0.35	0.35	0.35

4. One 20cm pant zipper for all sizes in all heights

5. One sew-on pants hook and eye

6. Matching thread, 5 spools (1 spool for the sewing machine and 4 spools for the overlocker)

## TOOLS AND EQUIPMENT

- Sewing machine for construction
- Overlocker for finishing raw edges. This may be replaced with a stretch overlock stitch or a zigzag stitch on the sewing machine (overlock or zigzag stitch width 2-3mm, stitch length 2.5mm)

## PATTERN PIECES LIST

*IMPORTANT! Don't forget to transfer all pattern notches onto the fabric.*

### 1. From main fabric:

- Front leg - cut 2
- Back leg - cut 2
- Right waistband - cut 2
- Left waistband - cut 2
- Fly shield- cut 1
- Belt loops - cut 1
- Front pocket welt - cut 2
- Front pocket facing - cut 2
- Top back pocket welt - cut 1
- Bottom back pocket welt - cut 1
- Back pocket facing - cut 1

### 2. From lining fabric:

- Back pocket lining - cut 2
- Front pocket facing - cut 2

### 3. From interfacing:

- Right waistband - cut 2
- Left waistband - cut 2
- Front pocket welt - cut 2
- Top back pocket welt - cut 1
- Bottom back pocket welt - cut 1

Cut out 3 interfacing rectangular strips to interface the pockets (shape and size specified on the pattern pieces) and 4 interfacing strips, 1.5 cm wide, to interface the inseam slit seam allowances (length according to the pattern pieces). The interfacing grainline runs parallel to the long side (along the selvedge of the fusible material).



Fully interface the 4 pieces of the contour waistband, 2 front pocket welts, and the top and bottom welts of the back pocket.

The left and right parts of the outer waistband (the outer and inner pieces of the waistband are to be marked respectively) must be additionally interfaced with the fusible seam tape along the waist edge and short end edges. Apply the fusible seam tape at 8mm from the edges. Make some notches along the edge of the seam tape to fit the rounded edges better.

To apply the interfacing, join the wrong side of the main piece (or section of the main piece) with the fusible side of the interfacing piece and press.



Make sure not to stretch the pieces with the iron. Use stamping movements rather than gliding: press the iron to the fabric, hold for some seconds, then move on to the next section of the garment piece. You can use a cotton pressing cloth to prevent the iron sole from sticking. To let the piece cool down and harden, leave it on a flat, hard surface for 15 minutes.