

FROM THE FOUNDER OF THE #VIKISEWS BRAND



Back in 2016, when I was working on my first set of sewing instructions, I was trying to write them in such a way that even a complete beginner could easily understand and use them to create their very first garment. These instructions laid the foundation for the Vikisews brand, its vision and its mission. I wanted to create modern patterns with the utmost detailed and clear instructions.

Now, with each new collection we are constantly improving our instructions, amending them and adding more relevant details. By the time the final product reaches you, our drafters, correctors, and editors would have spent weeks perfecting every word and every photograph. If you compile a few of our instructions together, you will get a sewing manual that will assist you in sewing all kinds of garments at any difficulty level.

And I would be very happy if these instructions helped you to turn your hobby into a lifelong passion... Enjoy the process! Create your ultimate dream wardrobe! Wear your garments proudly for years to come!

If you have any questions, please contact us at info@vikisews.com — we are always there to help.



HAIDA PATTERN DESCRIPTION

Haida is a semi-fitted A-line wrap skirt with a facing. The front and back feature waist darts and topstitched decorative flaps with rounded corners. The skirt fastens with buckles. Haida is fully lined and is above-the-knee length.



IMPORTANT!

The contents of this pattern are copyright protected and belong exclusively to Vikisews. You may use Vikisews patterns for personal use. It is prohibited to share Vikisews patterns and instructions with third parties, as well as to publish patterns and instructions online for public access. According to part 1 of clause 1252 and clause 1301 of the Civil Code of the Russian Federation, failure to comply with the mentioned rules constitutes a breach of the legislation in force in the field of copyright and entails liability of the violator. Illegal use or distribution will be prosecuted in accordance with legislation.

You may use Vikisews patterns for commercial use, to sew custom-made garments and/or create fashion collections, on the condition that the patterns are solely used in a manufacturing setting and are not further shared with individuals.

TOTAL EASE ALLOWANCE

	Waistline ease	Hipline ease
cm	3	5–6
inches	1 1/8	2–2 3/8

GARMENT LENGTH

Height, cm	Center back length, cm	Height, ft	Center back length, in
1 (154–160)	41.0	1 (5'1"–5'3")	16 1/8
2 (162–168)	43.0	2 (5'4"–5'6")	16 7/8
3 (170–176)	45.0	3 (5'7"–5'9")	17 3/4
4 (178–184)	47.0	4 (5'10"–6'1")	18 1/2

SUGGESTED FABRIC

To sew the skirt, choose suiting fabrics with the following properties:

- medium weight, malleable, soft, non-stretch or with very little stretch
- the fiber content can include natural fibers (wool, cotton), artificial fibers (viscose), blends (wool + silk, wool + polyester, cotton + viscose, etc.), and synthetics (polyester, polyester + elastane)
- the following fabrics are recommended: wool suiting, gabardine, corduroy, suede, faux leather

Attention! We do not recommend stretchy knits, thin fabrics (dress-weight wool) and heavyweight suiting (woven felt).

For the lining, we recommend artificial fibers (viscose), blends (viscose + elastane, viscose + polyester) or synthetics (polyester, polyester + elastane).

The garment in the photo is made of suiting. This fabric is medium weight, malleable, soft and with very little stretch. The fiber content is a blend of polyester, viscose and elastane.

The lining is 100% viscose.

TOOLS AND EQUIPMENT

- Sewing machine for construction
- Stitch-in-the-ditch foot (optional)
- Zipper foot to stitch buckles to the straps
- Eyelet press machine

PATTERN PIECES LIST

1. From main fabric:

- Back — cut 1 on fold
- Right front — cut 1
- Left front — cut 1
- Back facing — cut 1 on fold
- Center right front facing — cut 1
- Left front facing — cut 1
- Side right front facing — cut 1
- Back hem facing — cut 1 on fold
- Strap — cut 4
- Flap — cut 2

2. From lining fabric:

- Right front lining — cut 1
- Left front lining — cut 1
- Back lining — cut 1 on fold
- Flap lining — cut 2

IMPORTANT! Don't forget to transfer all pattern markings and notches onto the fabric.

3. From interfacing:

- Back facing — cut 1 on fold
- Center right front facing — cut 1
- Left front facing — cut 1
- Side right front facing — cut 1
- Back hem facing — cut 1 on fold
- Strap — cut 2
- Flap — cut 2
- Flap lining — cut 2

Cut from interfacing as well:

- Two 3 cm (1 5/8") wide strips (length according to the pattern) to interface the flap stitching lines
- Two 6 cm (2 3/8") wide strips (length according to the pattern) to interface the grown-on straps on the right and left front pieces. The grainline on the interfacing strips runs lengthwise (along the selvedge of the interfacing material).

SEAM ALLOWANCES

All pattern pieces include seam allowances: 1 cm (3/8") for all edges. Take this into account when laying out the pattern pieces on the fabric.


The eyelet placement shouldn't cause any pulling, folds, or creases.

Check for fit issues associated with individual features of the body.

After the fitting, mark changes symmetrically to both sides of the garment; if needed, baste once more for another fitting.



Pin the back darts and left front darts on the wrong side.



Machine-stitch the darts with backstitches at the beginning and end.

Press flat.