

# FROM THE FOUNDER OF THE #VIKISEWS BRAND

---



Back in 2016, when I was working on my first set of sewing instructions, I was trying to write them in such a way that even a complete beginner could easily understand and use them to create their very first garment. These instructions laid the foundation for the Vikisews brand, its vision and its mission. I wanted to create modern patterns with the utmost detailed and clear instructions.

Now, with each new collection we are constantly improving our instructions, amending them and adding more relevant details. By the time the final product reaches you, our drafters, correctors, and editors would have spent weeks perfecting every word and every photograph. If you compile a few of our instructions together, you will get a sewing manual that will assist you in sewing all kinds of garments at any difficulty level.

And I would be very happy if these instructions helped you to turn your hobby into a lifelong passion... Enjoy the process! Create your ultimate dream wardrobe! Wear your garments proudly for years to come!

If you have any questions, please contact us at [info@vikisews.com](mailto:info@vikisews.com) — we are always there to help.



## TRINITY PATTERN DESCRIPTION

---

Trinity is a fully lined semi-fitted coat with an accentuated waist. The shoulder line is extended. The coat is fitted with princess seams at the front and back. The front features a separate bottom part between the center front and mid back princess seams that forms a wide pocket. The coat has a grown-on stand collar and a double-breasted sew-on snap closure. The long set-in sleeves are semi-fitted and made up of two pieces. All the seams feature decorative topstitching. Trinity is below-knee length.



## IMPORTANT!

---

The contents of this pattern are copyright protected and belong exclusively to Vikisews. You may use Vikisews patterns for personal use. It is prohibited to share Vikisews patterns and instructions with third parties, as well as to publish patterns and instructions online for public access. **Non-compliance with the mentioned rules is a violation of the US copyright law and may result in civil liability and criminal prosecution.**

You may use Vikisews patterns for commercial use, to sew custom-made garments and/or create fashion collections, on the condition that the patterns are solely used in a manufacturing setting and are not further shared with individuals.

# TOTAL EASE ALLOWANCE

	Bust ease	Waistline ease	Hipline ease	Upper arm ease
cm	4.3–5.3	9.4–9.5	10.8–14.5	9.9–11.5
inches	1 3/4–2 1/8	3 3/4	4 1/4–5 3/4	3 7/8–4 1/2

# GARMENT LENGTH, SLEEVE LENGTH

Height, cm	Back length, cm	Sleeve length (estimated), cm
1 (154–160)	117.9–119.7	58.9–60.6
2 (162–168)	121.9–123.7	60.9–62.6
3 (170–176)	125.9–127.7	63–64.6
4 (178–184)	129.9–131.7	65–66.6

Height, ft	Back length, in	Sleeve length (estimated), in
1 (5'1"–5'3")	46 3/8–47 1/8	23 1/4–23 7/8
2 (5'4"–5'6")	48–48 3/4	24–24 5/8
3 (5'7"–5'9")	49 5/8–50 1/4	24 3/4–25 3/8
4 (5'10"–6'1")	51 1/8–51 7/8	25 5/8–26 1/4

# SUGGESTED FABRIC

To sew this coat, choose fabrics with the following properties:

- medium weight, low-stretch or non-stretch
- the fiber content can include polyurethane, polyvinyl chloride (PVC) with a woven or knit backing
- the following fabrics are recommended: faux leather

**Attention!** We do not recommend thin and soft faux leather.

For the lining, choose lining fabrics made of artificial fibers (viscose), blends (viscose + elastane, viscose + polyester), or synthetics (polyester, polyester + elastane).

# PATTERN PIECES LIST

---

## 1. From main fabric:

- center back — cut 2
- mid back — cut 2
- side back — cut 2
- center front — cut 2
- mid front — cut 2
- side front — cut 2
- bottom front — cut 2
- front facing — cut 2
- top sleeve — cut 2
- bottom sleeve — cut 2
- back neck facing — cut 1 on fold

## 2. From lining fabric:

- front lining — cut 2
- center back lining — cut 2
- side back lining — cut 2
- top sleeve lining — cut 2
- bottom sleeve lining — cut 2
- pocket lining — cut 2

## 3. From knit interfacing, 70 g/m<sup>2</sup>:

- center back — cut 2
- mid back — cut 2
- side back — cut 2
- center front — cut 2
- mid front — cut 2
- side front — cut 2
- bottom front — cut 2
- front facing — cut 2
- top sleeve — cut 2
- bottom sleeve — cut 2
- back neck facing — cut 1 on fold

**IMPORTANT!** Don't forget to transfer all pattern markings and notches onto the fabric.

## Also, partially interface the following:

- neckline and armhole seam allowances, hem allowance on the center back — 2 pieces
- armhole seam allowance, hem allowance on the mid back — 2 pieces
- armhole seam allowance on the side back — 2 pieces
- armhole seam allowance on the mid front — 2 pieces
- armhole seam allowance on the side front — 2 pieces
- hem allowance on the center front — 2 pieces
- sleeve cap seam allowance, hem allowance on the top sleeve — 2 pieces
- sleeve cap seam allowance, hem allowance on the bottom sleeve — 2 pieces

The grainline on the interfacing strips should match the grainline on the main pieces.

Additionally, cut two strips from interfacing. The length and width are specified on the bottom front pattern piece. The interfacing strips should be cut on the straight grain (parallel to the selvedge).

## 4. From one-way stretch interfacing, 50 g/m<sup>2</sup>:

- neckline seam allowance on the center front — 2 pieces

**IMPORTANT!** The interfacing is applied in two layers.





Remove the backing paper.



Press the seam allowances open using a pressing cloth. Press the seam allowances towards the right-hand center back piece.



Place the center back and mid back pieces right sides together and align the princess seam edges. Match the notches and pin. Machine-stitch, backstitching at the beginning and end.