

FROM THE FOUNDER OF THE #VIKISEWS BRAND



Back in 2016, when I was working on my first set of sewing instructions, I was trying to write them in such a way that even a complete beginner could easily understand and use them to create their very first garment. These instructions laid the foundation for the Vikisews brand, its vision and its mission. I wanted to create modern patterns with the utmost detailed and clear instructions.

Now, with each new collection we are constantly improving our instructions, amending them and adding more relevant details. By the time the final product reaches you, our drafters, correctors, and editors would have spent weeks perfecting every word and every photograph. If you compile a few of our instructions together, you will get a sewing manual that will assist you in sewing all kinds of garments at any difficulty level.

And I would be very happy if these instructions helped you to turn your hobby into a lifelong passion... Enjoy the process! Create your ultimate dream wardrobe! Wear your garments proudly for years to come!

If you have any questions, please contact us at info@vikisews.com — we are always there to help.



LAMMY PATTERN DESCRIPTION

Lammy is a semi-fitted top with a straight silhouette, featuring long raglan sleeves and a round neckline finished with a neckband. The top has a grown-on placket that fastens with snaps and is hip-length.



IMPORTANT!

The contents of this pattern are copyright protected and belong exclusively to Vikisews. You may use Vikisews patterns for personal use. It is prohibited to share Vikisews patterns and instructions with third parties, as well as to publish patterns and instructions online for public access. **Non-compliance with the mentioned rules is a violation of the US copyright law and may result in civil liability and criminal prosecution.**

You may use Vikisews patterns for commercial use, to sew custom-made garments and/or create fashion collections, on the condition that the patterns are solely used in a manufacturing setting and are not further shared with individuals.

TOTAL EASE ALLOWANCE

	Chest ease	Waistline ease	Hipline ease	Upper arm ease
cm	10–12	8.6–13.6	6.2–8.6	5.5–8.5
inches	3 7/8–4 3/4	3 3/8–5 3/8	2 1/2–3 3/8	2 1/8–3 3/8

GARMENT LENGTH, SLEEVE LENGTH

Height, cm	Back length including neckband width, cm	Sleeve length including part of shoulder and neckband width, cm
50	26.2–26.4	20–20.4
56	27.5–27.7	23.1–23.4
62	28.8–29	26.3–27
68	30.4–30.6	28.5–28.9
74	31.7–31.9	31.4–31.7
80	33.3–33.5	33.8–34.2
86	34.6–34.8	36.7–37.1
92	35.7–35.9	39.2–39.5

Height, in	Back length including neckband width, in	Sleeve length including part of shoulder and neckband width, in
19.75	10 3/8	7 7/8–8
22	10 7/8	9 1/8–9 1/4
24.5	11 3/8	10 3/8–10 5/8
26.75	12	11 1/4–11 3/8
29.25	12 1/2	12 3/8–12 1/2
31.5	13 1/8–13 1/4	13 1/4–13 1/2
33.75	13 5/8–13 3/4	14 1/2–14 5/8
36.25	14–14 1/8	15 3/8–15 1/2

IMPORTANT! When purchasing fabric, please account for shrinkage and buy 5% more than required.

2. Lightweight knit interfacing, 140 cm (55") wide, for all sizes and heights — 0.1 m (1/8 yd).
3. Two snap fasteners suitable for knit fabrics, 1 cm (3/8") in diameter.
4. Matching thread — 5 spools (1 spool for the sewing machine + 4 spools for the overlocker).

TOOLS AND EQUIPMENT

- sewing machine for construction
- overlocker for construction and finishing raw edges. This may be replaced with a stretch overlock stitch or a zigzag stitch on the sewing machine (overlock or zigzag stitch width 2–3 mm, stitch length 2.5 mm).
- coverstitch or coverlock machine for finishing the garment and sleeve hems. If you don't have a coverstitch machine, it can be replaced with a twin needle on any regular sewing machine that can do a zigzag stitch.
- press tool for installing snaps. This may be replaced with a snap fastener kit which includes a setting tool and snaps.

IMPORTANT! We recommend using specialty needles when working with knit fabrics (for example, *STRETCH*, *SUPER STRETCH*, *JERSEY*, etc.). These are ballpoint needles, so they part the threads of the fabric you are stitching rather than piercing them.

PATTERN PIECES LIST

1. From main fabric:

- front — cut 1
- back — cut 1 on fold
- left sleeve — cut 1
- right sleeve — cut 1
- neckband — cut 1.

2. From interfacing:

- front placket interfacing — cut 1
- sleeve placket interfacing — cut 1.

IMPORTANT! Don't forget to transfer all pattern markings and notches onto the fabric.



Finish the placket seam allowance on the left sleeve piece on the overlocker, keeping the right side of the piece facing up.



Trim the armhole seam allowances on the front and left sleeve pieces by 3 mm (1/8").



Place the front and left sleeve pieces right sides together. Align the armhole edges, match the notches, and pin.