

FROM THE FOUNDER OF THE #VIKISEWS BRAND



Back in 2016, when I was working on my first set of sewing instructions, I was trying to write them in such a way that even a complete beginner could easily understand and use them to create their very first garment. These instructions laid the foundation for the Vikisews brand, its vision and its mission. I wanted to create modern patterns with the utmost detailed and clear instructions.

Now, with each new collection we are constantly improving our instructions, amending them and adding more relevant details. By the time the final product reaches you, our drafters, correctors, and editors would have spent weeks perfecting every word and every photograph. If you compile a few of our instructions together, you will get a sewing manual that will assist you in sewing all kinds of garments at any difficulty level.

And I would be very happy if these instructions helped you to turn your hobby into a lifelong passion... Enjoy the process! Create your ultimate dream wardrobe! Wear your garments proudly for years to come!

If you have any questions, please contact us at info@vikisews.com - we are always there to help.



WENDY PATTERN DESCRIPTION

Wendy is a dress pattern for children with a close-fitting bodice, a voluminous skirt, and an empire waist. The round neckline is finished with a bias binding. The dress fastens with four buttons and buttonholes placed on the placket of the back bodice. Wendy has long, two-piece, raglan bishop sleeves. There is a channel at the bottom edge of the sleeves, with elastic threaded through it. The wide and straight skirt has gathers at the waist seam. The dress has an asymmetrical hemline — with the front shorter than the back. Wendy is below-knee length.



IMPORTANT!

The contents of this pattern are copyright protected and belong exclusively to Vikisews. You may use Vikisews patterns for personal use. It is prohibited to share Vikisews patterns and instructions with third parties, as well as to publish patterns and instructions online for public access. **Non-compliance with the mentioned rules is a violation of the US copyright law and may result in civil liability and criminal prosecution.**

You may use Vikisews patterns for commercial use, to sew custom-made garments and/or create fashion collections, on the condition that the patterns are solely used in a manufacturing setting and are not further shared with individuals.

TOTAL EASE ALLOWANCE

	Chest ease	Waistline ease	Hipline ease	Upper arm ease
cm	12–12.2	124.9–179.1	132.2–187.3	12–12.5
inches	4 3/4	49 1/8–70 1/2	52–73 3/4	4 3/4–4 7/8

GARMENT LENGTH, SLEEVE LENGTH

Height, cm	Back length, cm	Sleeve length including shoulder width, cm
98	57.4–57.5	40.3–40.9
104	61.4–61.5	42.9–43.4
110	66.5–66.6	45.4–45.9
116	72.5–72.6	47–47.5
122	77.6–77.8	53.2–53.6
128	82.6–83	55.4–57.2
134	86.8–87.2	59.3–61.2
140	91–91.4	62.2–64.3
146	95.2–95.6	66.1–68.3
152	100.2–100.6	68.6–70.9
158	106.1–106.3	75.8–77.1

Height, in	Back length, in	Sleeve length including shoulder width, in
38.5	22 5/8	15 7/8–16 1/8
41	24 1/8–24 1/4	16 7/8–17 1/8
43.25	26 1/8–26 1/4	17 7/8–18 1/8
45.5	28 1/2–28 5/8	18 1/2–18 3/4
48	30 1/2–30 5/8	21–21 1/8
50.5	32 1/2–32 5/8	21 3/4–22 1/2
52.75	34 1/8–34 3/8	23 3/8–24 1/8
55	35 7/8–36	24 1/2–25 3/8
57.5	37 1/2–37 5/8	26–26 7/8
60	39 1/2–39 5/8	27–27 7/8
62.25	41 3/4–41 7/8	29 7/8–30 3/8

PATTERN PIECES LIST

1. From main fabric:

- front bodice – cut 1 on fold
- back bodice – cut 2
- front sleeve – cut 2
- back sleeve – cut 2
- front skirt – cut 1 on fold
- back skirt – cut 1 on fold
- neckline binding – cut 1.

IMPORTANT! Don't forget to transfer all pattern markings and notches onto the fabric.

SEAM ALLOWANCES

All pattern pieces include seam allowances as follows:

- garment hem allowance – 2 cm (3/4")
- sleeve hem allowance – 2.5 cm (1")
- all other seams – 1 cm (3/8").

Take this into account when laying out pattern pieces on the fabric.



Press the seams flat.



Overlock the overarm seam allowances with the back sleeve piece facing up.

Overlock the underarm seam allowances with the front sleeve piece facing up.

Press the seams flat.



Press the overarm seam allowances toward the front sleeve, and the underarm seam allowances toward the back sleeve.