

SHELLY



3-14 years
HEIGHT 98-158 cm
(38.5"-62.25")

DIFFICULTY



ADVANCED

I M P O R T A N T !

The contents of this pattern are copyright protected and belong exclusively to Vikisews. You may use Vikisews patterns for personal use. It is prohibited to share Vikisews patterns and instructions with third parties, as well as to publish patterns and instructions online for public access. **Non-compliance with the mentioned rules is a violation of the US copyright law and may result in civil liability and criminal prosecution.**

You may use Vikisews patterns for commercial use, to sew custom-made garments and/or create fashion collections, on the condition that the patterns are solely used in a manufacturing setting and are not further shared with individuals.

S H E L L Y

#vikisews

PATTERN DESCRIPTION

Shelly is a loose-fitting single-breasted coat with a straight cut. It features a detachable hood and front patch pockets with pointed flaps that fasten with a button and buttonhole. The back features a yoke with a decorative button tab at the center. The coat has a drop shoulder and long, shirt-style, two-piece sleeves embellished with a tab at the hem, which fastens with a button and buttonhole. There are inseam pockets in the side seams and short slits at the hem. The coat has a turn-down collar with a collar stand and a center front button closure. The coat hem is curved and is longer at the back. Decorative topstitching accentuates the pocket flaps, sleeve tabs, back yoke tab, collar, yoke, inseam pocket openings, front edge, as well as garment hem and slits. The coat is fully lined and is below-hip length.



TOTAL EASE ALLOWANCE

| | Chest ease | Waistline ease | Hipline ease | Upper arm ease |
|--------|---------------|----------------|--------------|----------------|
| cm | 29.7-39 | 33.1-48.2 | 20.3-27.5 | 9.2-14.9 |
| inches | 11 3/4-15 3/8 | 13-19 | 8-10 7/8 | 3 5/8-5 7/8 |

GARMENT LENGTH, SLEEVE LENGTH

| Height, cm | Garment back length, cm | Sleeve length including shoulder width, cm |
|------------|-------------------------|--|
| 98 | 54.5 | 43-43.5 |
| 104 | 58.5 | 45.5-46 |
| 110 | 62.5 | 48.5-49 |
| 116 | 66.5 | 51-51.5 |
| 122 | 70.5 | 53.9-54.5 |
| 128 | 73.5 | 56.5-56.9 |
| 134 | 76.5 | 59-59.4 |
| 140 | 79.5 | 61.4-61.9 |
| 146 | 82.5 | 64-64.5 |
| 152 | 85.5 | 66.2-66.7 |
| 158 | 88.5 | 69.8-70 |

| Height, in | Garment back length, in | Sleeve length including shoulder width, in |
|------------|-------------------------|--|
| 38.5 | 21 1/2 | 16 7/8-17 1/8 |
| 41 | 23 | 17 7/8-18 1/8 |
| 43.25 | 24 5/8 | 19 1/8-19 1/4 |
| 45.5 | 26 1/8 | 20 1/8-20 1/4 |
| 48 | 27 3/4 | 21 1/4-21 1/2 |
| 50.5 | 28 7/8 | 22 1/4-22 3/8 |
| 52.75 | 30 1/8 | 23 1/4-23 3/8 |
| 55 | 31 1/4 | 24 1/8-24 3/8 |
| 57.5 | 32 1/2 | 25 1/4-25 3/8 |
| 60 | 33 5/8 | 26 1/8-26 1/4 |
| 62.25 | 34 7/8 | 27 1/2-27 1/2 |

SUGGESTED FABRIC

To sew this coat, choose coating fabrics with the following properties:

- medium-weight, pliable, breathable, soft, non-stretch or low-stretch, opaque
- the fiber content can include natural fibers (wool, silk, cotton, linen), artificial (viscose), blends (wool + silk, wool + polyester, cotton + viscose, etc.), and synthetic (polyester, polyester + elastane)
- the following fabrics are recommended: wool coating, cashmere, tweed, Melton wool, bouclé, jacquard, ponte di roma, felted wool.

Attention! We do not recommend stretchy knit materials (jersey fabrics), or lightweight sheer fabrics (organza, chiffon, stretch lace).

For the lining, use lining fabrics made from artificial fibers (viscose), blends (viscose + elastane, viscose + polyester), or synthetics (polyester, polyester + elastane).

For the hood, use knit fabrics made from natural fibers (cotton) and blends (cotton + viscose, cotton + polyester). The following types of knit fabrics are recommended: French terry, sweatshirt fleece.

The coat in the photos is made of tweed coating. The fabric is medium-weight, pliable, soft, and low-stretch. The fiber content is wool + viscose. The lining is 100% viscose. The detachable hood is made of French terry.

IMPORTANT!

When purchasing fabric, please account for shrinkage and buy 5% more than required.

6. 11 buttons, 2.3 cm (7/8") in diameter
7. 13 transparent buttons, 1 cm (3/8") in diameter
8. Matching thread - 2 spools
9. Matching topstitching thread (e.g. Madeira №35) - 1 spool

TOOLS AND EQUIPMENT

- sewing machine for construction
- buttonhole foot for the sewing machine
- edgestitch foot (optional)

PATTERN PIECES LIST

1. From main fabric:

- front - cut 2
- back - cut 1
- back yoke - cut 1
- front facing - cut 2
- top sleeve - cut 2
- bottom sleeve - cut 2
- undercollar - cut 2
- upper collar - cut 1
- collar stand - cut 2
- top sleeve tab - cut 2
- bottom sleeve tab - cut 2
- pocket - cut 2
- top pocket flap - cut 2
- bottom pocket flap - cut 2
- side pocket facing - cut 2
- back yoke tab - cut 2
- front hem facing - cut 2
- back hem facing - cut 1

2. From lining:

- front lining - cut 2
- back lining - cut 1
- back yoke lining - cut 1 on fold
- top sleeve lining - cut 2
- bottom sleeve lining - cut 2
- pocket lining - cut 2
- side pocket top lining - cut 2
- side pocket bottom lining - cut 2

3. From additional material:

- side hood - cut 2
- inner side hood - cut 2
- center hood panel - cut 1
- inner center hood panel - cut 1
- tie for channel - cut 1 on fold

4. From interfacing:

- front - cut 2
- back - cut 1
- back yoke - cut 1
- front facing - cut 2
- top sleeve (partly) - cut 2
- bottom sleeve (partly) - cut 2
- undercollar - cut 2
- upper collar - cut 1
- collar stand - cut 2

- top sleeve tab - cut 2
- bottom sleeve tab - cut 2
- pocket - cut 2
- top pocket flap - cut 2
- bottom pocket flap - cut 2
- side pocket facing - cut 2
- back yoke tab - cut 2
- front hem facing - cut 2
- back hem facing - cut 1

IMPORTANT!

Don't forget to transfer all pattern markings and notches onto the fabric.



- one edge of the side pocket facing
- all edges and foldline of the patch pocket
- outer edges on sleeve tabs
- outer edges on the top pocket flap
- outer edges on the back yoke tab

The fusible tape should be placed at 8 mm (3/8") from the edge and not stretched.

Thread trace the following constructive lines:

- center front
- center back and center yoke
- patch pocket and flap stitching lines
- button and buttonhole placement
- notches



Important! It's better to use light color thread to avoid dying the fabric when steaming.

