

HARPER

(for girls)



3-14 years
HEIGHT 98-158 cm
(38.5"-62.25")

DIFFICULTY



INTERMEDIATE

I M P O R T A N T !

The contents of this pattern are copyright protected and belong exclusively to Vikisews. You may use Vikisews patterns for personal use. It is prohibited to share Vikisews patterns and instructions with third parties, as well as to publish patterns and instructions online for public access. **Non-compliance with the mentioned rules is a violation of the US copyright law and may result in civil liability and criminal prosecution.**

You may use Vikisews patterns for commercial use, to sew custom-made garments and/or create fashion collections, on the condition that the patterns are solely used in a manufacturing setting and are not further shared with individuals.

H A R P E R

#vikisews

PATTERN DESCRIPTION

Harper is a loose-fitting hoodie with a straight cut. The edges of the lined hood overlap at the front. Two in-seam pockets are hidden in the princess seams on the front. The hoodie features a dropped shoulder and a shirt sleeve with two decorative seams. The cuffs and the waistband are made out of ribbing. The sleeve and shoulder seams, as well as the upper part of the sleeve cap, feature decorative topstitching. Harper is below-hip length.



TOTAL EASE ALLOWANCE

	Chest ease	Waistline ease	Hipline ease	Upper arm ease
cm	30-34	34-45	22-28	15.2-23
inches	11 3/4-13 3/8	13 3/8-17 3/4	8 5/8-11	6-9

GARMENT LENGTH, SLEEVE LENGTH

Height, cm	Center back length including waistband, cm	Sleeve length including shoulder width and cuff, cm
98	47.5	43.4-43.9
104	49.5	45.9-46.4
110	51.5	48.9-49.4
116	53.5	51.3-51.8
122	56.5	55.8-56.3
128	58.5	58.3-58.7
134	60.5	60.8-61.2
140	62.5	63.3-63.7
146	65.5	69-69.4
152	68.5	71.3-71.7
158	71.5	74.8-75

Height, in	Center back length including waistband, in	Sleeve length including shoulder width and cuff, in
38.5	18 3/4	17 1/8-17 1/4
41	19 1/2	18 1/8-18 1/4
43.25	20 1/4	19 1/4-19 1/2
45.5	21	20 1/4-20 1/2
48	22 1/4	22-22 1/8
50.5	23	23-23 1/8
52.75	23 3/4	23 7/8-24 1/8
55	24 1/2	24 7/8-25 1/8
57.5	25 3/4	27 1/8-27 3/8
60	27	28 1/8-28 1/4
62.25	28 1/4	29 1/2-29 1/2

SUGGESTED FABRIC

To sew this garment, choose knit fabrics with the following properties:

- soft, breathable, non-stretch or with very little stretch, medium-weight
- the fabric content can include natural (wool, cotton), artificial (viscose), blends (wool + polyester, cotton + polyester, cotton + elastane, etc.), and synthetic fibers (polyester, polyester + elastane)
- the following fabrics are recommended: thick French terry, sweatshirt fleece, ponte di roma.

Attention! We do not recommend lightweight sheer fabrics (chiffon, organza, stretch lace).

As an additional material for the cuffs and waistband we recommend using rib knits. For the lining of the hood, we recommend using cotton jersey.

The garment in the photo is made with sweatshirt fleece fabric. This fabric is medium-weight, soft, and has very little stretch. The fiber content is a blend of cotton and polyester. The waistband and cuffs are made out of ribbing.

The hood lining is cotton jersey.

PATTERN PIECES LIST

1. From main fabric:

- center front – cut 1 on fold
- side front - cut 2
- back - cut 1 on fold
- top sleeve - cut 2
- bottom back sleeve - cut 2
- bottom front sleeve - cut 2
- hood - cut 2
- pocket bag - cut 2.

2. From ribbing:

- cuff – cut 2
- front waistband - cut 1 on fold
- back waistband - cut 1 on fold.

3. From lining:

- hood lining – cut 2
- pocket lining - cut 2.

4. From interfacing:

- pocket opening seam allowances.

IMPORTANT!

Don't forget to transfer all pattern markings and notches onto the fabric.

The seam allowances are to be interfaced using strips of fusible interfacing 3.5 cm (1 3/8") wide and as long as the length of the pocket opening (measure on the pattern). The grainline should be parallel to the longer side of the strip (along the selvedge of the interfacing fabric).

As an alternative to strips of interfacing, use ready-made straight fusible tape 1 cm (3/8") wide.

SEAM ALLOWANCES

All pattern pieces include 1 cm (3/8") seam allowances around all edges.

Take this into account when laying out pattern pieces on the fabric.



Press the pocket-lining-to-side-front seam flat, and then press the seam allowances open. To secure the seam allowances, understitch at 2 mm along both sides of the seam. Backstitch in the beginning and end.



Place the pocket lining in lining fabric on top of the center front piece, right sides together. Align along the edges, pin.

With the center front piece facing up, stitch on the overlocker to sew the pocket lining in place.



Press the seam flat, and then press the seam allowances toward the lining.

Understitch the seam allowances to the pocket lining at 2 mm from the seam. Backstitch in the beginning and end. Press flat.



Join center and side front pieces along the segment of the pocket located in the princess seam, right sides together, and pin. Stitch on the sewing machine to join the pieces along the pocket seam allowance as follows:

- using a 3 mm stitch length, machine-stitch starting from the top downwards, breaking the stitching at the pocket opening upper notch, backstitch.
- using a 4 mm stitch length, machine-stitch along the pocket opening, backstitch.
- using a 3 mm stitch length, machine-stitch starting from the pocket opening bottom notch and breaking the stitching at the end of the seam allowance, backstitch.