FROM THE FOUNDER OF THE #VIKISEWS BRAND




Back in 2016, when I was working on my first set of sewing instructions, I was trying to write them in such a way that even a complete beginner could easily understand and use them to create their very first garment. These instructions laid the foundation for the Vikisews brand, its vision and its mission. I wanted to create modern patterns with the most detailed and clear instructions.

Now, with each new collection we are constantly improving our instructions, amending them and adding more relevant details. By the time the final product reaches you, our drafters, correctors, and editors would have spent weeks perfecting every word and every photograph. If you compile a few of our instructions together, you will get a sewing manual that will assist you in sewing all kinds of garments at any difficulty level.

And I would be very happy if these instructions helped you to turn your hobby into a lifelong passion... Enjoy the process! Create your ultimate dream wardrobe! Wear your garments proudly for years to come!

If you have any questions, please contact us at info@vikisews.com - we are always there to help.





CHRISTIAN PATTERN DESCRIPTION

Christian is a men's semi-fitted shirt jacket with a straight silhouette and a slightly dropped shoulder line. The two-piece long shirt sleeve features a slit with a placket down the elbow seam. The sleeves are finished with snapped cuffs. The front pieces have flapped gusset pockets at the chest and single-welt pockets on the sides. The back of the shirt jacket features a yoke. The shirt collar has a collar stand. The garment fastens with snaps at the center front placket. The jacket is insulated and fully lined, has a curved hem and is mid-hip length.



IMPORTANT!

The contents of this pattern are copyright protected and belong exclusively to Vikisews. You may use Vikisews patterns for personal use. It is prohibited to share Vikisews patterns and instructions with third parties, as well as to publish patterns and instructions online for public access. Non-compliance with the mentioned rules is a violation of the US copyright law and may result in civil liability and criminal prosecution.

You may use Vikisews patterns for commercial use, to sew custom-made garments and/or create fashion collections, on the condition that the patterns are solely used in a manufacturing setting and are not further shared with individuals.

TOTAL EASE ALLOWANCE

| | Chest ease | Waistline ease | Hipline ease | Upper arm ease |
|--------|-------------|----------------|--------------|----------------|
| cm | 26.7–27.1 | 36.4-40.5 | 21.6 | 14.2–14.5 |
| inches | 10 ½-10 5/8 | 14 3/8–16 | 8 ½ | 5 5/8-5 ¾ |

GARMENT LENGTH, SLEEVE LENGTH

| Height, cm | Garment length at center back, cm | Sleeve length including cuff, cm | Height, ft | Garment length at center back, in | Sleeve length including cuff, in |
|-------------|-----------------------------------|----------------------------------|---------------|-----------------------------------|----------------------------------|
| 1 (170-176) | 75.2 | 64.5 | 1 (5′7″–5′9″) | 29 ½ | 25 ½ |
| 2 (178-184) | 78.2 | 66.5 | 2 (5′10″–6′) | 30 ¾ | 26 ¼ |
| 3 (186-192) | 81.2 | 68.5 | 3 (6′1″–6′3″) | 32 | 27 |
| 4 (194-200) | 84.2 | 70.5 | 4 (6'4"-6'7") | 33 1/4 | 27 ¾ |

SUGGESTED FABRIC

To sew the Christian jacket, choose outerwear fabrics with the following properties:

- Lightweight or medium weight, non-stretch or with very little stretch, opaque, wind-proof and water-resistant
- The fiber content can include natural fibers (cotton), artificial (acetate), blends (cotton + polyester + viscose, etc.), and synthetic (polyester, polyester + elastane, terylene/dacron)
- The following fabrics are recommended: outerwear fabrics, such as gabardine, dewspo, taslan, membrane fabrics, taffeta, jordan, etc.

For the lining, we recommend artificial fibers (viscose), blends (viscose + elastane, viscose + polyester) or synthetic (polyester, polyester + elastane). For the insulation, use polyester batting, such as Thinsulate, alpolux, isosoft 100g/m2, etc.

The garment in the photo is made of outerwear fabric. This fabric is medium weight and non-stretch. The fiber content is 100% polyester. The lining fabric is a blend of viscose and polyester. The insulation used is sintepon 100 g/m2.

TOOLS AND EQUIPMENT

- Sewing machine for construction
- Stitch-in-the-ditch foot for your sewing machine (optional)
- Snap press machine (optional)

PATTERN PIECES LIST

- 1. From main fabric:
- Front cut 2
- Placket cut 2
- · Back cut 1 on fold
- · Back yoke cut 1 on fold
- Top sleeve cut 2
- · Bottom sleeve cut 2
- Cuff cut 2
- Sleeve placket cut 2
- Upper collar cut 1 on fold
- · Undercollar cut 1 on fold
- · Collar stand cut 2
- · Gusset pocket cut 2
- Pocket gusset cut 2
- Gusset pocket top flap cut 2
- Gusset pocket bottom flap cut 2
- Bottom pocket welt cut 2
- Bottom pocket bag with grown-on facing cut 2
- · Back hem facing cut 1 on fold
- · Back neck facing cut 1 on fold
- Front hem facing cut 2

2. From lining fabric:

- Front lining cut 2
- Back lining cut 1 on fold
- Top sleeve lining cut 2
- · Bottom sleeve lining cut 2
- Gusset pocket lining cut 2
- Gusset lining cut 2
- · Bottom pocket bag cut 2

IMPORTANT! Don't forget to transfer all pattern markings and notches onto the fabric.



For convenience, mark the welt seam line at 1cm (3/8") from the edge and the sides. Align the welt's fold with the line you've drawn before. Pin the welt to the garment piece.



Stitch the welt onto the front, backstitching at the beginning and end of the stitching line.

For better positioning of the pocket bag and grown-on facing piece, mark its seam line at a distance of 1cm (3/8") from the welt, as shown in the photo.



Put the pocket bag with the right side to the welt piece and baste. Put the pocket bag with grown-on facing piece with the right side to the front piece, as shown in the photo, matching the edge with the line you've drawn before. Pin or baste. Stitch on the sewing machine, backstitching at the beginning and end of the stitching line.