FROM THE FOUNDER OF THE #VIKISEWS BRAND



Back in 2016, when I was working on my first set of sewing instructions, I was trying to write them in such a way that even a complete beginner could easily understand and use them to create their very first garment. These instructions laid the foundation for the Vikisews brand, its vision and its mission. I wanted to create modern patterns with the utmost detailed and clear instructions.

Now, with each new collection we are constantly improving our instructions, amending them and adding more relevant details. By the time the final product reaches you, our drafters, correctors, and editors would have spent weeks perfecting every word and every photograph. If you compile a few of our instructions together, you will get a sewing manual that will assist you in sewing all kinds of garments at any difficulty level.

And I would be very happy if these instructions helped you to turn your hobby into a lifelong passion... Enjoy the process! Create your ultimate dream wardrobe! Wear your garments proudly for years to come!

If you have any questions, please contact us at info@vikisews.com — we are always there to help.



ABBIE PATTERN DESCRIPTION

Abbie is a semi-fitted jacket with a straight silhouette. The front features bust darts transferred to the bottom edge and shoulder seams. The bust darts transferred to the bottom edge are designed as princess seams with pockets in them. The center front edge is finished with a decorative placket. The jacket closes with a separating zipper that has a windproof placket backing. The back is fitted with darts at the bottom edge. The jacket has a turn-down collar with a separate collar stand and long, set-in, semi-fitted, two-piece sleeves with a slight flare towards the bottom. Abbie is above-hip length.



IMPORTANT!

The contents of this pattern are copyright protected and belong exclusively to Vikisews. You may use Vikisews patterns for personal use. It is prohibited to share Vikisews patterns and instructions with third parties, as well as to publish patterns and instructions online for public access. Non-compliance with the mentioned rules is a violation of the US copyright law and may result in civil liability and criminal prosecution.

You may use Vikisews patterns for commercial use, to sew custom-made garments and/or create fashion collections, on the condition that the patterns are solely used in a manufacturing setting and are not further shared with individuals.

TOTAL EASE ALLOWANCE

	Bust ease	Waistline ease	Upper arm ease
cm	20.3–21	44.2–46.1	9.2–10.4
inches	8-8 1/4	17 3/8–18 1/8	3 5/8-4 1/8

GARMENT LENGTH, SLEEVE LENGTH

Height, cm	Back length, cm	Sleeve length including shoulder width, cm
1 (154–160) 2 (162–168) 3 (170–176) 4 (178–184)	50.4–54.9 53.4–57.9 56.4–60.9 59.4–63.9	72–74.7 74–76.7 76–78.7 78–80.7
Height, ft	Back length, in	Sleeve length including shoulder width, in

SUGGESTED FABRIC

To sew this jacket, choose medium pile faux fur with the following properties:

- · medium weight, structured, non-stretch or with very little stretch
- the fiber content can include natural fibers (wool), blends (wool + polyester), and synthetics (polyester)
- the following fabrics are recommended: faux fur with knit backing, faux fur with woven backing, napped coating fabrics, bouclé fabrics

Attention! We do not recommend using thin coating fabrics or faux fur that doesn't hold its shape.

As an additional fabric, we recommend using non-stretch fabrics, such as outerwear fabrics, faux leather, and faux suede.

PATTERN PIECES LIST

1. From main fabric:

- front cut 2
- · back cut 1 on fold
- top sleeve cut 2
- · bottom sleeve cut 2
- · upper collar cut 1 on fold
- · undercollar cut 2
- · collar stand cut 2
- pocket facing cut 4

2. From additional fabric:

- front facing cut 2
- · back neck facing cut 1 on fold
- inner placket cut 2
- placket cut 2

3. From lining fabric:

- front lining cut 2
- back lining cut 2
- top sleeve lining cut 2
- bottom sleeve lining cut 2
- pocket lining cut 4

IMPORTANT! Don't forget to transfer all pattern markings and notches onto the fabric.

4. From interfacing:

- · upper collar cut 1 on fold
- · undercollar cut 2
- · collar stand cut 2
- front facing cut 2
- back neck facing cut 1 on fold
- · inner placket cut 2
- placket cut 2

Additionally, interfacing must be applied along the bottom edge, according to the paper pattern, on the following pieces:

- top sleeve cut 2
- · bottom sleeve cut 2
- ∙ back cut 1
- front cut 2

5. From insulation:

· inner placket — cut 1

SEAM ALLOWANCES

All pattern pieces include seam allowances as follows:

- garment hem allowance 4 cm (1 5/8")
- sleeve hem allowance 4 cm (1 5/8")
- all other edges -1 cm (3/8")

Take this into account when laying out pattern pieces on the fabric.



Stitch the darts, backstitching at the beginning and end.

Press the seams flat.

Clip each dart open along the fold, stopping 1.5 cm (5/8") short of the dart point.



Trim the pile off the seam allowances.



Press the seam allowances open using a pressing cloth.