

**DIRECT ACTING
SOLENOID VALVE
SERIES KL - KLE**



SERIES KL - KLE HIGH FLOW RATES IN A COMPACT DESIGN



BENEFITS

Reduced installation times



Large range of models (2/2, 3/2, UNI)
with compact dimensions

**Easy and flexible
to install in the system**



Electrical connectors with
monostable or bistable manual override

Energy efficient



High flow rate
compared to its size

**Enhanced machine
performance and productivity**



Extended version
for further improved performance

High reliability



More than 90 million cycles

**Components compliant
with medical devices**



OX1 version

**Compact design and reduced weight
for portable devices**



Miniaturisation

The latest Series KL and KLE miniaturised 10mm solenoid valves have been designed for industrial applications and medical devices that require high flow rates and pressures within compact dimensions.

Its compact design, reduced weight and low energy consumption makes the KL version the ideal solution for applications within confined spaces and limited power supply, such as portable oxygen concentrators or emergency lung ventilators. For applications that demand more robust levels of performance, the KLE version has been designed to control higher pressures and flow rates compared to traditional solenoid valves.

The body size and overall dimensions of both versions have been designed to allow easy integration with manifold systems or subbases and to be quickly installed on devices and machines.

Series KL and KLE are available in different models to satisfy any application across all the main sectors of industrial automation and life science.

TECHNOLOGIES



Motion Control



Fluid Control

SECTORS



Industrial automation



Life Science

General data

TECHNICAL FEATURES

Function	2/2 NC - 3/2 NC - 3/2 NO - 3/2 UNI
Operation	direct acting poppet type
Pneumatic connections	on subbase
Orifice diameter	0.6 ... 1.6 mm
Flow coefficient kv (l/min)	0.12 ... 0.50
Operating pressure	0 ÷ 3 ... 9 bar
Operating temperature	0 ÷ 50 °C
Media	filtered compressed air, unlubricated, according to ISO 8573-1 class 3.4.3, inert gas
Response time	ON <10 ms - OFF <10 ms
Manual override	monostable or bistable - only for 3/2 versions
Installation	in any position

MATERIALS IN CONTACT WITH MEDIUM

Body	PBT
Seals	FKM
Internal parts	stainless steel - brass

ELECTRICAL FEATURES

Voltage	5 ... 24 V DC - other voltages on demand
Voltage tolerance	±10%
Power consumption	1 W - 1.3/0.3 W - 4/1 W
Duty cycle	ED 100%
Electrical connection	connector mod. 121-8... - M8 connector mod. CS... (the M8 connection of the valve accepts polarity reversal)
Protection class	IP50 with connector 121-8... - IP65 with M8 connector

Contacts

Camozzi Automation S.p.A.

Società Unipersonale
Via Eritrea, 20/I
25126 Brescia
Italy
Tel. +39 030 37921
info@camozzi.com

Customer Service

Tel. +39 030 3792790
service@camozzi.com

Export Department

Tel. +39 030 3792253
sales@camozzi.com

