

# Rational SelfCooking Centre 5 Senses



## Rational SCC 5 Senses



- SelfCookingControl® with 7 cooking modes – meat, poultry, fish, side dishes, egg dishes, baked products, Finishing®
- Efficient LevelControl® (ELC®) – mixed loads with individual rack monitoring and load-specific time adjustment for every rack
- Combi-Steamer Mode with 3 modes – steam 30°C - 130°C, hot air 30°C - 300°C, combination of steam and hot air 30°C - 300°C
- ClimaPlus Control® – humidity measured, set and regulated to one percent accuracy
- Automatic Finishing® – processes for plated banquets, buffets, à la carte, etc.
- Delta-T cooking for gently cooking large joints
- The patented HiDensityControl® redefines cooking quality, giving 30% more capacity and 20% less energy consumption



An ISO 9001:2015  
Accredited Company



#### THE LEGAL STUFF:

Subject to any applicable laws from time to time:

(1) All the product images shown are for marketing purposes and may differ from the actual product.

(2) All factual information was correct at the time of going to print and is subject to change without prior notice.

Errors and Omissions Excepted. Vulcan and its Marketing Agency do not accept responsibility or liability for any incorrect listing of any merchandise.

Tel: 011 249 8500

[www.vulcan.co.za](http://www.vulcan.co.za)

# Rational SelfCooking Centre 5 Senses



## Model SCC 61

## Model SCC 62



Capacity: 6 x 1/1 GN  
 Number of Meals per Day: 30 - 80 (Guide only)  
 Lengthwise Loading: 1/1, 1/2, 2/3, 1/3, 2/8 GN  
 Width: 847mm  
 Depth: 771mm  
 Height: 782mm  
 Water Inlet: R 3/4"  
 Water Outlet: DN 50  
 Water Pressure: 150 - 600kPa or 0.15 - 0.6mPa

Capacity: 6 x 2/1 GN  
 Number of Meals per Day: 60 - 160 (Guide only)  
 Lengthwise Loading: 2/1, 1/1 GN  
 Width: 1.069mm  
 Depth: 971mm  
 Height: 782mm  
 Water Inlet: R 3/4"  
 Water Outlet: DN 50  
 Water Pressure: 150 - 600kPa or 0.15 - 0.6mPa

**Electric:**  
 Product Code: 2611242  
 Weight: 110kg  
 Mains Connection: 3 NAC 400V  
 Fuse: 3 x 16A  
 "Dry Heat" Connection: 10.3kW  
 "Moist Heat" Connection: 9kW  
 Cable Cross-Section: 5 x 2.5mm<sup>2</sup>

**Electric:**  
 Product Code: 2611173  
 Weight: 142kg  
 Mains Connection: 3 NAC 400V  
 Fuse: 3 x 32A  
 "Dry Heat" Connection: 21.8kW  
 "Moist Heat" Connection: 18kW

**Gas:**  
 Product Code (LPG): 2611171  
 Product Code (NG): 2611172  
 Weight: 126kg  
 Height (Incl. Draft Converter): 1.021mm  
 Electricity Connection: 0.3kW  
 Fuse: 1 x 16A  
 Mains Connection: 1 NAC 230V  
 Gas Supply/Connection: R 3/4"  
 Natural Gas/LPG: Liquid gas  
 Max. Rated Thermal Load: 13kW/14kW  
 "Dry Heat" Connection: 13kW/14kW  
 "Moist Heat" Connection: 12kW/13kW

**Gas:**  
 Product Code (LPG): 2611174  
 Product Code (NG): 2611175  
 Weight: 168kg  
 Height (Incl. Draft Converter): 1.021mm  
 Electricity Connection: 0.4kW  
 Fuse: 1 x 16A  
 Mains Connection: 1 NAC 230V  
 Gas Supply/Connection: R 3/4"  
 Natural Gas/LPG: Liquid gas  
 Max. Rated Thermal Load: 28kW/31kW  
 "Dry Heat" Connection: 28kW/31kW  
 "Moist Heat" Connection: 21kW/23kW



**THE LEGAL STUFF:**

*Subject to any applicable laws from time to time:*

(1) All the product images shown are for marketing purposes and may differ from the actual product.

(2) All factual information was correct at the time of going to print and is subject to change without prior notice.

Errors and Omissions Excepted. Vulcan and its Marketing Agency do not accept responsibility or liability for any incorrect listing of any merchandise.

Tel: 011 249 8500

[www.vulcan.co.za](http://www.vulcan.co.za)

# Rational SelfCooking Centre 5 Senses



## Model SCC 101

## Model SCC 102



Capacity: 10 x 1/1 GN  
 Number of Meals per Day: 80 - 150 (Guide only)  
 Lengthwise Loading: 1/1, 1/2, 2/3, 1/3, 2/8 GN  
 Width: 847mm  
 Depth: 771mm  
 Height: 1042mm  
 Water Inlet: R 3/4"  
 Water Outlet: DN 50  
 Water Pressure: 150 - 600kPa or 0.15 - 0.6mPa

Capacity: 10 x 2/1 GN  
 Number of Meals per Day: 150 - 300 (Guide only)  
 Lengthwise Loading: 2/1, 1/1 GN  
 Width: 1.069mm  
 Depth: 971mm  
 Height: 1042mm  
 Water Inlet: R 3/4"  
 Water Outlet: DN 50  
 Water Pressure: 150 - 600kPa or 0.15 - 0.6mPa

**Electric:**  
 Product Code: 2611244  
 Weight: 135.5kg  
 Mains Connection: 3 NAC 400V  
 Fuse: 3 x 32A  
 "Dry Heat" Connection: 18kW  
 "Moist Heat" Connection: 8kW

**Electric:**  
 Product Code: 2611246  
 Weight: 182kg  
 Mains Connection: 3 NAC 400V  
 Fuse: 3 x 63A  
 "Dry Heat" Connection: 36kW  
 "Moist Heat" Connection: 36kW

**Gas:**  
 Product Code (LPG): 2611177  
 Product Code (NG): 2611178  
 Weight: 154.5kg  
 Height (Incl. Draft Converter): 1.281mm  
 Electricity Connection: 0.39kW  
 Fuse: 1 x 16A  
 Mains Connection: 1 NAC 230V  
 Gas Supply/Connection: R 3/4"  
 Natural Gas/LPG: Liquid gas  
 Max. Rated Thermal Load: 22kW/24kW  
 "Dry Heat" Connection: 22kW/24kW  
 "Moist Heat" Connection: 20kW/22kW

**Gas:**  
 Product Code (LPG): 2611180  
 Product Code (NG): 2611181  
 Weight: 198kg  
 Height (Incl. Draft Converter): 1.281mm  
 Electricity Connection: 0.6kW  
 Fuse: 1 x 16A  
 Mains Connection: 1 NAC 230V  
 Gas Supply/Connection: R 3/4"  
 Natural Gas/LPG: Liquid gas  
 Max. Rated Thermal Load: 45kW/50kW  
 "Dry Heat" Connection: 45kW/50kW  
 "Moist Heat" Connection: 40kW/44kW



**THE LEGAL STUFF:**

Subject to any applicable laws from time to time:

(1) All the product images shown are for marketing purposes and may differ from the actual product.

(2) All factual information was correct at the time of going to print and is subject to change without prior notice.

Errors and Omissions Excepted. Vulcan and its Marketing Agency do not accept responsibility or liability for any incorrect listing of any merchandise.

Tel: 011 249 8500  
[www.vulcan.co.za](http://www.vulcan.co.za)

# Rational SelfCooking Centre 5 Senses



## Model SCC 201

## Model SCC 202



Capacity: 20 x 1/1 GN  
 Number of Meals per Day: 150 - 300 (Guide only)  
 Lengthwise Loading: 2/1, 1/1 GN  
 Width: 879mm  
 Depth: 791mm  
 Height: 1.782mm  
 Water Inlet: R 3/4"  
 Water Outlet: DN 50  
 Water Pressure: 150 - 600kPa or 0.15 - 0.6mPa

Capacity: 20 x 2/1 GN  
 Number of Meals per Day: 150 - 300 (Guide only)  
 Lengthwise Loading: 1/1, 1/2, 2/3, 1/3, 2/8 GN  
 Width: 1.084mm  
 Depth: 996mm  
 Height: 1.782mm  
 Water Inlet: R 3/4"  
 Water Outlet: DN 50  
 Water Pressure: 150 - 600kPa or 0.15 - 0.6mPa

**Electric:**  
 Product Code: 2611248  
 Weight: 258kg  
 Mains Connection: 3 NAC 400V  
 Fuse: 3 x 63A  
 "Dry Heat" Connection: 36kW  
 "Moist Heat" Connection: 36kW

**Electric:**  
 Product Code: 2611250  
 Weight: 332kg  
 Mains Connection: 3 NAC 400V  
 Fuse: 3 x 100A  
 "Dry Heat" Connection: 64.2kW  
 "Moist Heat" Connection: 54kW

**Gas:**  
 Product Code (LPG): 2611180  
 Product Code (NG): 2611181  
 Weight: 286kg  
 Height (Incl. Draft Converter): 2.021mm  
 Electricity Connection: 0.7kW  
 Fuse: 1 x 16A  
 Mains Connection: 1 NAC 230V  
 Gas Supply/Connection: R 3/4"  
 Natural Gas/LPG: Liquid gas  
 Max. Rated Thermal Load: 44kW/48kW  
 "Dry Heat" Connection: 44kW/48kW  
 "Moist Heat" Connection: 38kW/40kW

**Gas:**  
 Product Code (LPG): 2611183  
 Product Code (NG): 2611184  
 Weight: 370.5kg  
 Height (Incl. Draft Converter): 2.021mm  
 Electricity Connection: 1.1kW  
 Fuse: 1 x 16A  
 Mains Connection: 1 NAC 230V  
 Gas Supply/Connection: R 3/4"  
 Natural Gas/LPG: Liquid gas  
 Max. Rated Thermal Load: 90kW/100kW  
 "Dry Heat" Connection: 90kW/100kW  
 "Moist Heat" Connection: 51kW/56kW



**THE LEGAL STUFF:**

Subject to any applicable laws from time to time:

(1) All the product images shown are for marketing purposes and may differ from the actual product.

(2) All factual information was correct at the time of going to print and is subject to change without prior notice.

Errors and Omissions Excepted. Vulcan and its Marketing Agency do not accept responsibility or liability for any incorrect listing of any merchandise.

Tel: 011 249 8500

www.vulcan.co.za